

## ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

### M057781 Cata CeilingTunable White - 24W - 2700 K/5700 K



**ДИЗАЙН:**

Carlotta de Bevilacqua

**МАТЕРИАЛЫ:**

**ОПИСАНИЕ:**

Interchangeable optical unit through a 'twist & lock' mechanism. Defined, concentrated light beams thanks to an innovative collimation system.

2 beam angles: 2x3,5°, 2x8°.

Excellent quality of light: Cata Tuneable White: adjustable colour temperature from 2700K to 5700K CRI >93 (min.) Cata Stable White: available as warm white (3000K) and neutral white (4000K) – CRI=80 (min.).

Rotation of 360°, tilt angle of +90°/-90° 2 installation options: with adaptor for 3-circuit track, or base plate for ceiling mounting. Ultra-flat power source (8mm height): DALI dimmable as standard, DALI8 interface hub for Tuneable White version.

Materials : optic in transparent and metallic polycarbonate, heat sink in die-cast gloss aluminium, feeder/power supply in transparent polycarbonate, arm in die-cast gloss aluminium.

Complies with standard EN60598-

24W - 2700 K/5700 K

ВЫБРАТЬ

LED

Polished aluminium

КОД ПРОДУКТА

M057781

Вид светового потока



Dimmable

ТЕХНИЧЕСКИЕ ДАННЫЕ

**ХАРАКТЕРИСТИКИ**

Наименование продукции: M057781 Cata CeilingTunable White - 24W - 2700 K/5700 K  
Код: M057781  
Цвет: Polished aluminium  
Серии: Architectural  
место контракта: Музеи & Выставки

**РАЗМЕРЫ**

Высота: cm 17.6  
Диаметр: cm 13  
Диаметр базы: cm 13  
Угол наклона: 9090  
Вращение: 360  
Вес: kg 0.8


**ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ**

Категория: LED  
Ватт: 18W  
Световой поток (lm): 1400-1550  
Типология: 2  
Цветовая температура (K): 2700-5700  
Класс: A

**LUMINAIR**

Watt: 24W

**РАЗМЕРЫ**



**ЦВЕТ**




АКСЕССУАРЫ



Optical unit 2x6° M057500



Optical unit 2x12° M057600



NYACata1

