

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Ego 55S DL 14° 3000K - Steel



ДИЗАЙН:

Nord Light
2011

МАТЕРИАЛЫ:

ОПИСАНИЕ:

Light fixture with high-performance LED light sources. Ceiling installation. Two different housing depths. Round and square version in five sizes. Consists of body, frame, black silkscreened tempered glass, fixing springs. Body in EN AB44100 aluminium, silicone gaskets. Frame in aluminium or stainless steel AISI 316. Black silkscreened tempered glass, 8mm-thick. Fixing springs in harmonic iron. Power connection to the mains by means of a H05RN-r cabl and IP68 electrical terminal board, supplied with the fixture. Glass surface temperature lower than 40°C. Fixed optics. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 2 colour temperatures Warm = 3000K Neutral = 4000K Painted die-cast aluminium with 3-stage outdoortreatment: nanotechnologies, anti-oxidant primer, polyester paint. Technical features of light fixtures in compliance with EN60598-1 and part 2-13. IP Rating IP65. Insulation class III. Installation must be carried out by specialized personnel. Carefully follow the instructions.

Spot optic Concentrated luminous flow to highlight details avoiding unwanted light dispersion.

ВЫБРАТЬ

LED

Steel

КОД ПРОДУКТА

T4060SPW00

Вид светового потока

IP65/67

ТЕХНИЧЕСКИЕ ДАННЫЕ


ХАРАКТЕРИСТИКИ

Наименование продукции: Ego 55S DL 14° 3000K - Steel
Код: T4060SPW00
Цвет: Steel
Серии: Nord Light, Outdoor

РАЗМЕРЫ

Длина базы: cm 5,5
Ширина базы: cm 5,5
Глубина встройки: cm 9,4
Форма отверстия: Квадратная форма
Ударопрочность: IK10

РАЗМЕРЫ



ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED
Ватт: 1,2W
Световой поток (lm): 83lm
Количество: 1 x 1
Типология: 1
Цветовая температура (K): 3000 K
Класс: A

ЦВЕТ



LUMINAIR

ПРА: Electronic ballast supplied separately
Watt: 1,5W

АКСЕССУАРЫ



ALIMENTATORE 25W 24V DC
T409996

ALIMENTATORE 60W 24V DC
T409998

ALIMENTATORE 90W 24V DC
T409999