

## ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

### Ego 55R DL 14° 3000K - Aluminium



#### ДИЗАЙН:

Nord Light  
2011

#### МАТЕРИАЛЫ:

#### ОПИСАНИЕ:

Light fixture with high-performance LED light sources. Ceiling installation. Two different housing depths. Round and square version in five sizes. Consists of body, frame, black silkscreened tempered glass, fixing springs. Body in EN AB44100 aluminium, silicone gaskets. Frame in aluminium or stainless steel AISI 316. Black silkscreened tempered glass, 8mm-thick. Fixing springs in harmonic iron. Power connection to the mains by means of a H05RN-r cabl and IP68 electrical terminal board, supplied with the fixture. Glass surface temperature lower than 40°C. Fixed optics. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 2 colour temperatures Warm = 3000K Neutral = 4000K Painted die-cast aluminium with 3-stage outdoortreatment: nanotechnologies, anti-oxidant primer, polyester paint. Technical features of light fixtures in compliance with EN60598-1 and part 2-13. IP Rating IP65. Insulation class III. Installation must be carried out by specialized personnel. Carefully follow the instructions.

Spot optic Concentrated luminous flow to highlight details avoiding unwanted light dispersion.

#### ВЫБРАТЬ

LED

Aluminium

#### КОД ПРОДУКТА

T4081SPW00

#### Вид светового потока

IP65/67

#### ТЕХНИЧЕСКИЕ ДАННЫЕ


##### ХАРАКТЕРИСТИКИ

Наименование продукции: Ego 55R DL 14° 3000K - Aluminium  
Код: T4081SPW00  
Цвет: Aluminium  
Серии: Nord Light, Outdoor

##### РАЗМЕРЫ

Диаметр: cm 5.5  
Диаметр отверстия: cm 4.7  
Глубина встройки: cm 9.4  
Форма отверстия: Круглая форма  
Ударопрочность: IK10

##### РАЗМЕРЫ



##### ЦВЕТ



##### ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED  
Ватт: 1,2W  
Световой поток (lm): 83lm  
Типология: 1  
Цветовая температура (K): 3000K  
Класс: A

##### LUMINAIR

ПРА: Electronic ballast supplied separately  
Watt: 1,5W

#### АКСЕССУАРЫ



ALIMENTATORE 25W 24V DC



ALIMENTATORE 60W 24V DC



ALIMENTATORE 90W 24V DC

T409996

T409998

T409999