

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Ego Flat 150R DL 6°x54° 4000K Alluminium

**ДИЗАЙН:**

Artemide
2011

МАТЕРИАЛЫ:**ОПИСАНИЕ:**

Light fixture with high-performance LED light sources. Ceiling installation. Two different housing depths. Round and square version in five sizes. Consists of body, frame, black silkscreened tempered glass, fixing springs. Body in EN AB44100 aluminium, silicone gaskets. Frame in aluminium or stainless steel AISI 316. Black silkscreened tempered glass, 8mm-thick. Fixing springs in harmonic iron. Power connection to the mains by means of a H05RN-r cabl and IP68 electrical terminal board, supplied with the fixture. Glass surface temperature lower than 40°C. Fixed optics. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 2 colour temperatures Warm = 3000K Neutral = 4000K Painted die-cast aluminium with 3-stage outdoortreatment: nanotechnologies, anti-oxidant primer, polyester paint. Technical features of light fixtures in compliance with EN60598-1 and part 2-13. IP Rating IP65. Insulation class III. Installation must be carried out by specialized personnel. Carefully follow the instructions.

Flood opticWide luminous flow suitable for lighting large areas.

ВЫБРАТЬ**КОД ПРОДУКТА**


T42005ELPTN00

Вид светового потока**ТЕХНИЧЕСКИЕ ДАННЫЕ****ХАРАКТЕРИСТИКИ**

Наименование продукции: Ego Flat 150R DL 6°x54°
4000K Alluminium
Код: T42005ELPTN00
Цвет: Aluminium
Серии: Nord Light, Outdoor

РАЗМЕРЫ

Диаметр: cm 15
Глубина встройки: cm 6
Форма отверстия: Круглая форма
Ударопрочность: IK10

РАЗМЕРЫ**ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ**

Категория: LED
Ватт: 6W
Световой поток (lm): 392lm
Типология: 1
Цветовая температура (K): 4000K
Класс: A

ЦВЕТ**LUMINAIR**

ПРА: Electronic ballast supplied separately
Watt: 6W

АКСЕССУАРЫ

ALIMENT. 13,5W 500mA IP67
NL19046

ALIMENT. 20W 500mA IP67
NL19047

