

## ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

### Falange 18 - 54°x6° 3000K



#### ДИЗАЙН:

Wilmotte & Industries  
2012

#### МАТЕРИАЛЫ:

Painted aluminum, tempered glass

#### ОПИСАНИЕ:

Adjustable light fixture with direct emission, with high-performance LED light sources. Ground, wall, eaves installation. 2 sizes: 134 x 134, 238 x 134 mm. Composed by adjustable lighting unit and support (housing the wiring). Rotation on the base +/-180°, body tilt +/-100° by means of a graduated metal ring allowing an accurate adjustment. Positioning is maintained by means of locking dowels. Body and support in EN AB44100 aluminium, silicone gaskets. Electronic ballast integrated in the body. Silkscreened tempered glass siliconed to a secondary frame. Wiring to be carried out by means of plug IP 68.

#### ВЫБРАТЬ

LED

gray

#### КОД ПРОДУКТА

NL30001ELK002

#### Вид светового потока

IP65

#### ТЕХНИЧЕСКИЕ ДАННЫЕ

##### ХАРАКТЕРИСТИКИ

Наименование продукции: Falange 18 - 54°x6° 3000K  
Код: NL30001ELK002  
Цвет: gray  
Материал: Painted aluminum, tempered glass  
Серии: Nord Light, Outdoor

##### РАЗМЕРЫ

Длина: cm 23.8  
Ширина: cm 10.5  
Высота: cm 21.4


##### ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED  
Ватт: 44W  
Световой поток (lm): 2182lm  
Количество: 1 x 16  
Типология: 1  
Цветовая температура (K): 3000K  
Класс: A

##### LUMINAIR

Watt: 44W  
Напряжение: 220-240 Vac

##### РАЗМЕРЫ



##### ЦВЕТ

