


ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Kalifa II Suspension 1200 Direct Emission - T16 1x54W dimmable - White



ДИЗАЙН:

Ernesto Gismondi

МАТЕРИАЛЫ:

Extruded Aluminium

ОПИСАНИЕ:

Single pendant light with direct lighting using 28W and 54W T16 fluorescent light source. Extruded aluminium body with a white or grey paint finish, available in lengths of 1188mm and 2400mm. Super pure aluminium optics. Light output ratio: 82%. DARK LIGHT emission is in compliance with EN12464-1 standard. Electronic control gear, with or without dimming control. Emergency lighting on request. Quick adjustment steel suspension cables.

ВЫБРАТЬ

FLUO

White

КОД ПРОДУКТА

M166921

Вид светового потока



IP20


Dimmable

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Kalifa II Suspension 1200 Direct Emission - T16 1x54W dimmable - White
 Код: M166921
 Цвет: White
 Материал: Extruded Aluminium
 Серии: Architectural

РАЗМЕРЫ



ОПТИКА

Вид светового потока: Dual or Direct Emission

РАЗМЕРЫ

Длина: cm 118
 Ширина: cm 8
 Высота: cm 9.3
 Вес: kg 5.1
 тест раскаленной проволокой: 960 °

ЦВЕТ



ЛАМПЫ НЕ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: FLUO
 Количество: 1
 Lbs: T16(G5)
 Ватт: 54W
 Цоколь: G5
 Тип: FDH-54
 Световой поток (lm): 4450lm
 Цветопередача: 85
 Цветовая температура (K): 3000K
 Продолжительность (h): 20000h

LUMINAIR

ПРА: Electronic dimmable DALI Integrated
 Watt: 1x54W
 Напряжение: 220V-240V