

## ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

### LineaLed Wallwasher 6LED - 40 ° 3000K



#### ДИЗАЙН:

Carlotta de Bevilacqua  
2011

#### МАТЕРИАЛЫ:

Aluminium, transparent tempered glass.

#### ОПИСАНИЕ:

Walk-over and drive-over recessed floor installation. Composed by body in extruded aluminium, protection glass; provided with junction box for input/output connection. Body fastened to the recessing box by means of proper pre-stressed steel springs supplied with the fixture.

24Vdc remote ballast.

Connect a maximum number of 10 fixtures in a continuous line.

Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions.

#### Flood optic

Wide luminous flow suitable for lighting large areas. (40° optic)

#### ВЫБРАТЬ

LED

Alluminium

#### КОД ПРОДУКТА

NL17320ELK0

#### Вид светового потока



65/67


#### Dimmable

#### ТЕХНИЧЕСКИЕ ДАННЫЕ

##### ХАРАКТЕРИСТИКИ

Наименование продукции: LineaLed Wallwasher 6LED  
- 40 ° 3000K  
Код: NL17320ELK0  
Цвет: Alluminium  
Материал: Aluminium, transparent  
tempered glass.  
Серии: Nord Light, Outdoor  
место контракта: Фасады зданий

##### РАЗМЕРЫ



##### РАЗМЕРЫ

Длина: cm 30  
Ширина: cm 4.8  
Высота: cm 6.5  
Ударопрочность: IK07

##### ЦВЕТ



##### ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED  
Ватт: 12W  
Световой поток (lm): 444lm  
Количество: 1 x 6  
Типология: 1  
Цветовая температура (K): 3000K  
Класс: A  
Напряжение: 24 Vdc

##### LUMINAIR

ПРА: Elettronic  
Watt: 8,4 W  
Напряжение: 24 Vdc

#### АКСЕССУАРЫ



80 x 50 x 1,5mm  
staffa di giunzione  
continuity joint



46,5 x 62,5 x 1,5mm  
testata cassaforma  
housing end cap

No Image  
Available

No Image  
Available

LINEALED STAFFA  
GIUNZIONE C/CASSA NL75810

LINEALED TESTATA  
CASSA(COPPIA) NL74890

ALIMENT. 40W 24Vdc IP67  
NL62040

ALIMENT. 70W 24Vdc IP67  
NL89080



ALIMENT. 150W 24Vdc IP67  
NL62880

CONTROCASSA LINEALED  
WALLWASHER 30 NL17325H0

CONNETTORE  
ALIMENTAZIONE + TAPPO  
NL19052