

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

LineaLed Wallwasher 6LED - 40 ° 4000K



ДИЗАЙН:

Carlotta de Bevilacqua
2011

МАТЕРИАЛЫ:

Aluminium, transparent tempered glass.

ОПИСАНИЕ:

Walk-over and drive-over recessed floor installation. Composed by body in extruded aluminium, protection glass; provided with junction box for input/output connection. Body fastened to the recessing box by means of proper pre-stressed steel springs supplied with the fixture.

24Vdc remote ballast.

Connect a maximum number of 10 fixtures in a continuous line.

Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions.

Flood optic

Wide luminous flow suitable for lighting large areas. (40° optic)

ВЫБРАТЬ

LED

Alluminium

КОД ПРОДУКТА

NL17320ELW0

Вид светового потока



65/67

Dimmable

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: LineaLed Wallwasher 6LED
- 40 ° 4000K
Код: NL17320ELW0
Цвет: Alluminium
Материал: Aluminium, transparent
tempered glass.
Серии: Nord Light, Outdoor
место контракта: Фасады зданий

РАЗМЕРЫ



РАЗМЕРЫ

Длина: cm 30
Ширина: cm 4.8
Высота: cm 6.5
Ударопрочность: IK07

ЦВЕТ



ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED
Ватт: 12W
Световой поток (lm): 480 m
Количество: 1 x 6
Типология: 1
Цветовая температура (K): 4000K
Класс: A
Напряжение: 24Vdc

LUMINAIR

ПРА: Elettronic
Watt: 8,4 W
Напряжение: 24 Vdc

АКСЕССУАРЫ



80 x 50 x 1,5mm
staffa di giunzione
continuity joint



46,5 x 62,5 x 1,5mm
testata cassaforma
housing end cap

No Image
Available

No Image
Available

LINEALED STAFFA
GIUNZIONE C/CASSA NL75810

LINEALED TESTATA
CASSA(COPPIA) NL74890

ALIMENT. 40W 24Vdc IP67
NL62040

ALIMENT. 70W 24Vdc IP67
NL89080



ALIMENT. 150W 24Vdc IP67
NL62880



CONTROCASSA LINEALED
WALLWASHER 30 NL17325H0



CONNETTORE
ALIMENTAZIONE + TAPPO
NL19052