

## ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

### LineaLed Wallwasher 12LED - 40 ° 3000K



#### ДИЗАЙН:

Carlotta de Bevilacqua  
2011

#### МАТЕРИАЛЫ:

Aluminium, transparent tempered glass.

#### ОПИСАНИЕ:

Walk-over and drive-over recessed floor installation. Composed by body in extruded aluminium, protection glass; provided with junction box for input/output connection. Body fastened to the recessing box by means of proper pre-stressed steel springs supplied with the fixture.

24Vdc remote ballast.

Connect a maximum number of 5 fixtures in a continuous line.

Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions.

#### Flood optic

Wide luminous flow suitable for lighting large areas. (40° optic)

#### ВЫБРАТЬ

LED

Alluminium

#### КОД ПРОДУКТА

NL17321ELK0

#### Вид светового потока



65/67

#### Dimmable

#### ТЕХНИЧЕСКИЕ ДАННЫЕ


##### ХАРАКТЕРИСТИКИ

Наименование продукции:	LineaLed Wallwasher 12LED - 40 ° 3000K
Код:	NL17321ELK0
Цвет:	Alluminium
Материал:	Aluminium, transparent tempered glass.
Серии:	Nord Light, Outdoor
место контракта:	Фасады зданий

##### РАЗМЕРЫ

Длина:	cm 50
Ширина:	cm 4.8
Высота:	cm 6.5
Ударопрочность:	IK07

##### ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

	Категория:	LED
	Ватт:	16,8W
	Световой поток (lm):	888lm
	Количество:	1 x 12
	Типология:	1
	Цветовая температура (K):	3000K
	Класс:	A
	Напряжение:	24Vdc

##### LUMINAIR

ПРА:	Electronic
Watt:	16,8 W
Напряжение:	24 Vdc

##### РАЗМЕРЫ



##### ЦВЕТ



#### АКСЕССУАРЫ



80 x 50 x 1,5mm  
staffa di giunzione  
continuity joint



46,5 x 62,5 x 1,5mm  
testata cassaforma  
housing end cap

No Image  
Available

No Image  
Available

LINEALED STAFFA  
GIUNZIONE C/CASSA NL75810

LINEALED TESTATA  
CASSA(COPPIA) NL74890

ALIMENT. 40W 24Vdc IP67  
NL62040

ALIMENT. 70W 24Vdc IP67  
NL89080



ALIMENT. 150W 24Vdc IP67  
NL62880

CONTROCASSA LINEALED  
WALLWASHER 50 NL17326H0

CONNETTORE  
ALIMENTAZIONE + TAPPO  
NL19052