

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

LineaLed Wallwasher 18LED - 10° 3000K



ДИЗАЙН:

Carlotta de Bevilacqua
2011

МАТЕРИАЛЫ:

Aluminium, transparent tempered glass.

ОПИСАНИЕ:

Walk-over and drive-over recessed floor installation. Composed by body in extruded aluminium, protection glass; provided with junction box for input/output connection. Body fastened to the recessing box by means of proper pre-stressed steel springs supplied with the fixture.

24Vdc remote ballast.

Connect a maximum number of 3 fixtures in a continuous line.

Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions.

Spot optic (10° optic)

Concentrated luminous flow to highlight details avoiding unwanted light dispersion.

ВЫБРАТЬ

LED

Alluminium

КОД ПРОДУКТА

NL1732210K0

Вид светового потока



65/67

Dimmable

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: LineaLed Wallwasher
18LED - 10° 3000K
Код: NL1732210K0
Цвет: Alluminium
Материал: Aluminium, transparent
tempered glass.
Серии: Nord Light, Outdoor
место контракта: Фасады зданий

РАЗМЕРЫ

Длина: cm 78
Ширина: cm 4.8
Высота: cm 6.5
Ударопрочность: IK07


ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED
Ватт: 25,2W
Мощность (каждый): 1W
Световой поток (lm): 1334 lm
Количество: 1 x 18
Типология: 1
Цветовая температура (K): 3000K
Класс: A
Напряжение: 24 Vdc

LUMINAIR

ПРА: Elettronic
Watt: 25,2 W
Напряжение: 24 Vdc

РАЗМЕРЫ



ЦВЕТ





80 x 50 x 1,5mm
staffa di giunzione
continuity joint

LINEALED STAFFA
GIUNZIONE C/CASSA NL75810



46,5 x 62,5 x 1,5mm
testata cassaforma
housing end cap

LINEALED TESTATA
CASSA(COPPIA) NL74890



ALIMENT. 40W 24Vdc IP67
NL62040



ALIMENT. 70W 24Vdc IP67
NL89080



ALIMENT. 150W 24Vdc IP67
NL62880



CONTROCASSA LINEALED
WALLWASHER 80 NL17327H0



CONNETTORE
ALIMENTAZIONE + TAPPO
NL19052