

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

LineaLed Wallwasher 24LED - 40 ° 4000K



ДИЗАЙН:

Carlotta de Bevilacqua
2011

МАТЕРИАЛЫ:

Aluminium, transparent tempered glass.

ОПИСАНИЕ:

Walk-over and drive-over recessed floor installation. Composed by body in extruded aluminium, protection glass; provided with junction box for input/output connection. Body fastened to the recessing box by means of proper pre-stressed steel springs supplied with the fixture.

24Vdc remote ballast.

Connect a maximum number of 2 fixtures in a continuous line.

Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions.

Flood optic

Wide luminous flow suitable for lighting large areas. (40° optic)

ВЫБРАТЬ

LED

Alluminium

КОД ПРОДУКТА

NL17323ELW0

Вид светового потока



65/67

Dimmable

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции:	LineaLed Wallwasher 24LED - 40 ° 4000K
Код:	NL17323ELW0
Цвет:	Alluminium
Материал:	Aluminium, transparent tempered glass.
Серии:	Nord Light, Outdoor
место контракта:	Фасады зданий

РАЗМЕРЫ

Длина:	cm 97.8
Ширина:	cm 4.8
Высота:	cm 6.5
Ударопрочность:	IK07

ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория:	LED
Ватт:	33,6W
Световой поток (lm):	1920 lm
Количество:	1 x 6-12-18-24
Типология:	1
Цветовая температура (K):	4000 K
Класс:	A
Напряжение:	24 Vdc

LUMINAIR

ПРА:	Electronic
Watt:	33,6 W
Напряжение:	24 Vdc

РАЗМЕРЫ



ЦВЕТ



АКСЕССУАРЫ



80 x 50 x 1,5mm
staffa di giunzione
continuity joint



46,5 x 62,5 x 1,5mm
testata cassaforma
housing end cap

No Image
Available

No Image
Available

LINEALED STAFFA
GIUNZIONE C/CASSA NL75810

LINEALED TESTATA
CASSA(COPPIA) NL74890

ALIMENT. 40W 24Vdc IP67
NL62040

ALIMENT. 70W 24Vdc IP67
NL89080



ALIMENT. 150W 24Vdc IP67
NL62880

LINEALED C/CASSA 98CM
NL76680

CONNETTORE
ALIMENTAZIONE + TAPPO
NL19052