

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Luceri 220 +emergency - 2x18W - Grey



ДИЗАЙН:

Artemide

МАТЕРИАЛЫ:

Technopolymer

ОПИСАНИЕ:

A range of recessed downlights fluorescent lamps. Body made from technopolymers. Reflector in vacuum-metallised polycarbonate with anti-scratch surface treatment. Decorative ring made from aluminium or injection moulded plastic, available in 2 colour options, with or without screen. Fitting is made by one quarter turn rotation. The luceri screen dark light optic ensures a controlled luminance level of less than 200 cd/m² for an observation angle of 65° or above with respect to the vertical axis, well within the limits set by standard EN12464-1. Low recess depth for ceilings of 1mm to 35mm thick. Electronic ballast and emergency lighting. Electrical connection by means of quick connectors. Bridging connection possible. Complies with standard EN60598-1 and other specific standards.

Comes complete with plastic front and anti-dazzle cross-blade. IP20 = recessed part / IP23 = external part

ВЫБРАТЬ

FLUO

Grey

КОД ПРОДУКТА

L596860

Вид светового потока

IP29/IP23



ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Luceri 220 +emergency - 2x18W - Grey
 Код: L596860
 Цвет: Grey
 Материал: Technopolymer
 Серии: Architectural
 Окружающая среда: Внутреннее место контракта:


ОПТИКА

Вид светового потока: Direct

РАЗМЕРЫ

Длина: cm 39
 Высота: cm 11.5
 Диаметр: cm 23.5
 Глубина встройки: cm 14.5
 Форма отверстия: Круглая форма
 Вес: kg 1.7


РАЗМЕРЫ



ЦВЕТ



ЛАМПЫ НЕ ВКЛЮЧЕНЫ В КОМПЛЕКТ

 Категория: FLUO
 Количество: 2
 Lbs: Tc-del
 Ватт: 18W
 Цоколь: G24q-2
 Тип: Fsh
 Световой поток (lm): 1200lm
 Цветопередача: 1b
 Цветовая температура (K): 3000K
 Продолжительность (h): 12000h

LUMINAIR

ПРА: Electronic
 Watt: 2x18W
 Наличие аварийной батареи: Integrated
 Напряжение: 220V-240V

