

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Luceri 220 Screen Quick Reference - 2x26W - White



ДИЗАЙН:

Artemide

МАТЕРИАЛЫ:

Technopolymer

ОПИСАНИЕ:

A range of recessed downlights fluorescent lamps. Body made from technopolymers. Reflector in vacuum-metallised polycarbonate with anti-scratch surface treatment. Decorative ring made from aluminium or injection moulded plastic, available in 2 colour options, with or without screen. Fitting is made by one quarter turn rotation. The luceri screen dark light optic ensures a controlled luminance level of less than 200 cd/m² for an observation angle of 65° or above with respect to the vertical axis, well within the limits set by standard EN12464-1. Low recess depth for ceilings of 1mm to 35mm thick. Electronic ballast and emergency lighting. Electrical connection by means of quick connectors. Bridging connection possible. Complies with standard EN60598-1 and other specific standards.

Comes complete with open plastic front.
IP20= recessed part
IP23 = external part

ВЫБРАТЬ

FLUO

White

КОД ПРОДУКТА

L597710

Вид светового потока

IP20/23

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Luceri 220 Screen Quick Reference - 2x26W - White
Код: L597710
Цвет: White
Материал: Technopolymer
Серии: Architectural
Окружающая среда: Внутреннее место контракта:


ОПТИКА

Вид светового потока: Diffused And Direct

РАЗМЕРЫ

Длина: cm 39
Диаметр: cm 23.5
Глубина встройки: cm 17
Форма отверстия: Круглая форма
Вес: kg 0.9


РАЗМЕРЫ



ЦВЕТ



ЛАМПЫ НЕ ВКЛЮЧЕНЫ В КОМПЛЕКТ

 Категория: FLUO
Количество: 2
Lbs: TC-DEL
Ватт: 26W
Цоколь: G24q-3
Тип: FSQ-26
Световой поток (lm): 1800lm
Цветопередача: 85
Цветовая температура (K): 3000K
Продолжительность (h): 12000h

LUMINAIR

ПРА: Electronic
Watt: 2x26W
Напряжение: 220V-240V