

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Nota Bene Suspension 2400 - T16 2x54W - Grey



ДИЗАЙН:

Artemide

МАТЕРИАЛЫ:

Painted Steel

ОПИСАНИЕ:

Pendant system with direct-indirect lighting using 28W and 54W T16 fluorescent lamps. Available as a single pendant light or as a modular system. Steel body with a white or grey paint finish, available in lengths of 1234mm and 2416mm. Dark light optic made from super pure aluminium. Dark light emission is in compliance with EN12464-1 standard, with average luminance levels lower than the 1000 cd/m² limit for an observation angle of 65° or above with respect to the vertical axis. Light output ratio: 91% (1xT16) and 87% (2xT16). Light distribution: 65% indirect and 35% direct (1xT16), 63% indirect and 37% direct (2xT16). Electronic ballast or Dali-Switchdim dimmable electronic ballast. The system comprises of power supply units with ceiling plate and power supply cable, and continuity modules. Intermodule mechanical connection by linear or 90° connectors. Electrical connection via quick connectors. Quick adjustment steel suspension cables. Complies with standard EN60598-1 and other specific standards.

ВЫБРАТЬ

FLUO

Grey

КОД ПРОДУКТА

M107290

Вид светового потока



IP20




ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Nota Bene Suspension
2400 - T16 2x54W - Grey
Код: M107290
Цвет: Grey
Материал: Painted Steel
Серии: Architectural
Окружающая среда: Внутреннее
место контракта:

РАЗМЕРЫ



ОПТИКА

Вид светового потока: Indirect/Direct

РАЗМЕРЫ

Длина: cm 241
Ширина: cm 16
Высота: cm 4.8
Вес: kg 7.9
тест раскаленной проволокой: 850 °

ЦВЕТ



ЛАМПЫ НЕ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: FLUO
Количество: 2
Lbs: T16(G5)
Ватт: 54W
Цоколь: G5
Тип: FDH-54
Световой поток (lm): 4450lm
Цветопередача: 85
Цветовая температура (K): 3000K
Продолжительность (h): 20000h

LUMINAIR

ПРА: Electronic Integrated
Watt: 2x54W
Напряжение: 220V-240V