

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Nota Bene Suspension 2400 - T16 4x28-54W Dimmable - Grey



ДИЗАЙН:

Artemide

МАТЕРИАЛЫ:

Painted Steel

ОПИСАНИЕ:

Pendant system with direct-indirect lighting using 28W and 54W T16 fluorescent lamps. Available as a single pendant light or as a modular system. Steel body with a white or grey paint finish, available in lengths of 1234mm and 2416mm. Dark light optic made from super pure aluminium. Dark light emission is in compliance with EN12464-1 standard, with average luminance levels lower than the 1000 cd/m² limit for an observation angle of 65° or above with respect to the vertical axis. Light output ratio: 91% (1xT16) and 87% (2xT16). Light distribution: 65% indirect and 35% direct (1xT16), 63% indirect and 37% direct (2xT16). Electronic ballast or Dali-Switchdim dimmable electronic ballast. The system comprises of power supply units with ceiling plate and power supply cable, and continuity modules. Intermodule mechanical connection by linear or 90° connectors. Electrical connection via quick connectors. Quick adjustment steel suspension cables. Complies with standard EN60598-1 and other specific standards.

ВЫБРАТЬ

FLUO

Grey

КОД ПРОДУКТА

M107391

Вид светового потока



IP20

Dimmable

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Nota Bene Suspension
2400 - T16 4x28-54W
Dimmable - Grey

Код: M107391


Цвет: Grey

Материал: Painted Steel

Серии: Architectural

Окружающая среда: Внутреннее место контракта:

РАЗМЕРЫ



ОПТИКА

Вид светового потока: Indirect/Direct

РАЗМЕРЫ

Длина: cm 241

Ширина: cm 16

Высота: cm 4.8

Вес: kg 8.1

тест раскаленной проволокой: 850 °

ЦВЕТ



ЛАМПЫ НЕ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: FLUO

Количество: 4

Lbs: T16(G5)

Ватт: 54W

Цоколь: G5

Тип: FDH-54

Световой поток (lm): 4450lm

Цветопередача: 85

Цветовая температура (K): 3000K

Продолжительность (h): 20000h

LUMINAIR

ПРА: Electronic Dimmable DALI
Integrated

Watt: 4x28/54W

Напряжение: 220V-240V



INTERACTIVE-DALI remote control. M104900



INTERACTIVE-DALI kit Ø86mm, white, recessed. Can be connected to a max. 11 DALI dimmable units. Is operated through INTERACTIVE-DALI remote control or external push button. M074030