

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Nothing86System Prewired LED 46W Diffuser Gear-Plate - Direct



ДИЗАЙН:

Ernesto Gismondi

МАТЕРИАЛЫ:

ОПИСАНИЕ:

A versatile modular lighting system for linear diffused or dark light emission and freely configurable accent lighting. Composed of structural modules in extruded aluminium, prewired gear plates and optics systems. 3 types of installation: recessed, surface mounting and suspended. Structural modules available in 12 different lengths of up to 4736mm, specially designed to allow the lighting designer to alternate as freely as possible different light sources. The lighting sequence can also evolve over time to meet new arrangements, as long as it remains compatible with the initial total length installed. Linear fluorescent, led and metal halide technologies can be freely alternated. Prewired gear plates with quick-connectors, with direct fluorescent or LED lighting equipment, and indirect fluorescent illumination. 2 options of fluorescent diffused lighting available: T16-seamless lamps or conventional T16 lamps with overlapping arrangement for uninterrupted light lines without dark spots. 2 LED equipment options: monochromatic with warm white or neutral white emission, and RGB. Angular configurations possible by means of junction angles on the same plane or on 2 perpendicular planes (on request). Simple installations can be managed with "all-in-one" fixtures (nothing 86Stand-Alone) already pre-configured and fully accessorized. Complies with standard EN60598-1 and other specific standards.

Includes 3-poles through-wiring with quick-connector. LED power supply and DALI or DMX control unit to be ordered separately.

ВЫБРАТЬ

LED

N/s

КОД ПРОДУКТА

M237800

Вид светового потока



ТЕХНИЧЕСКИЕ ДАННЫЕ		
ХАРАКТЕРИСТИКИ		ЦВЕТ
Наименование продукции:	Nothing86System Prewired LED 46W Diffuser Gear-Plate - Direct	<input type="checkbox"/>
Код:	M237800	
Цвет:	N/s	
Серии:	Architectural	
Окружающая среда:	Внутреннее	
РАЗМЕРЫ		
Длина:	cm 236	
ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ		
Категория:	LED	
Ватт:	40W	
Световой поток (lm):	4880lm	
Типология:	1	
Цветовая температура (K):	3000K	
Класс:	A	
LUMINAIR		
ПРА:	Electronic Integrated	
Watt:	46W	
Напряжение:	220V-240V	

АКСЕССУАРЫ



Electronic power supply. IP67. Input voltage range: 90-264VAC / 47-63Hz. Output voltage: 48VDC. Protection against overcurrent, overvoltage, short-circuit and



LV
re, with
art. 100W. For
total 90W.
M075000

Electronic power supply. IP67. Input voltage range: 90-264VAC / 47-63Hz. Output voltage: 48VDC. Protection against overcurrent, overvoltage, short-circuit and



LV
re, with
art. 240W. For
total 225W.
M075100

ELECT. CONVERTER 230-240V/48V 320X IP67 M076100



LV

Interfaccia di controllo compatibile DALI switch dim 310X168X90 mm. IP67 M077000



Interfaccia di controllo compatibile DALI switch dim o DMX 310X168X90 mm. IP67 M077100



Interfaccia di controllo compatibile DALI switch dimper montaggio su barra DIN 106X90X70 mm. IP20 M077200



Interfaccia di controllo compatibile DALI switch dim o DMX per montaggio su barra DIN 106X90X70 mm. IP67 M077300



ALGO/NOTHING86SYSTEM - Supplementary through-wiring. 3 poles. Length 1184mm. M198800



ALGO/NOTHING86SYSTEM - Supplementary through-wiring. 3 poles. Length 2368mm. M199000



ALGO/NOTHING86SYSTEM - Supplementary through-wiring. 7 poles. Length 1184mm. M198700



ALGO/NOTHING86SYSTEM - Supplementary through-wiring. 7 poles. Length 2368mm. M198900



ALGORITMO/NOTHING86SYSTEM - Feeding kit. Allows to connect the mains to the first pre-wired gear plate of the initial module. 3 poles (for feeding LED gear plates). M073230

ALGORITMO/NOTHING86SYSTEM - Feeding kit. Allows to connect the mains to the first pre-wired gear plate of the initial module. 7 poles (for feeding fluorescent gear plates). M073240

Raccordo su un piano per la continuità tra moduli LED a emissione diffusa e tra moduli spot. M167500

