

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Nothing Downlight 105mm - 52° - 4000K - fix



ДИЗАЙН:

Ernesto Gismondi
2005

МАТЕРИАЛЫ:

Die-cast Aluminium

ОПИСАНИЕ:

Fixed downlight $\varnothing 105\text{mm}$ using 12V dichroic halogen light source. Recessing ring made from aluminium. Remote transformer. Optional white ring in injection moulded plastic for an installation without plaster finish coat (fitting by one quarter turn rotation). Complies with standard EN60598-1 and other specific standard. Created with the purpose of making the lighting fixture disappear completely into the false ceiling as to solely draw attention to the lighting effects, nothing recessed is a complete range of recessed luminaires, whose installation requires a finish coat of plaster.

ВЫБРАТЬ

LED

КОД ПРОДУКТА

M065300

Вид светового потока



ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Nothing Downlight 105mm - 52° - 4000K - fix

Код: M065300

Материал: Die-cast Aluminium

Серии: Architectural

Окружающая среда: Внутреннее

место контракта: Гостеприимство
Гостиницы, Розничные магазины, Офисы, Частные резиденции

ОПТИКА

Вид светового потока: Direct Adjustable

РАЗМЕРЫ

Диаметр: cm 16

Глубина встройки: cm 12.7

Форма отверстия: Круглая форма

Вес: kg 0.6

тест раскаленной проволокой: 960 °

ЛАМПЫ НЕ ВКЛЮЧЕНЫ В КОМПЛЕКТ

LED

Категория: LED

Ватт: 12W

Световой поток (lm): 1060lm

Типология: 1

Цветовая температура (K): 4000K

Класс: A

LUMINAIR

ПРА: Electronic Remote

Watt: 12W

РАЗМЕРЫ

Ø105

Ø160

127

АКСЕССУАРЫ



NOTHING RECESSED ROUND

ELECTRONIC BALLAST-UNIT

Electronic transformer 230-

Electronic transformer 230-

Ø105 - Ring in injection
moulded plastic. Ø165mm.
White finish. M064900

"SLIM" FOR HIT 35W. Dim.
150x62x30mm. M070032

240V/12V. Class II. Dimmable
by trailing or leading edge
external dimmers. 10-60W.
123x32x23mm. M070211

240V/12V. Class II. Dimmable
by trailing or leading edge
external dimmers. 35-105W.
102x51x30mm. M070412