

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Pad 230V Track - 14,5W 4000K - 36°



ДИЗАЙН:

Carlotta de Bevilacqua
2010

МАТЕРИАЛЫ:

Aluminium, plastic

ОПИСАНИЕ:

Series of projectors using high-efficiency led with monochromatic warm white (3000K) and neutral white (4000K) emission. Comprised of an aluminium body with bright anodized finish and a translucent cover in polycarbonate. Pad is available in four mounting options: with three-phase track adapter, with base plate or recessed plate for ceiling mounting, and in combination with the Algoritmo product line. The array of 12 leds (13W in total) lays on a metal core placed on the aluminium body of the projector that acts as heat dissipator. The special power supply system is housed within the body, thus allowing a direct connection to the electrical network (100-240V). The cover acts as a support for the lenses available in 3 beam options. It provides a diffused lighting effect while ensuring protection for the electrical parts. A smart hinge that combines reduced dimensions with a very large angular excursion provides extreme flexibility of rotation: rotation of up to 358°, tilt angle of up to +90°/-90°. Versions with surface ceiling plate and recessed ceiling plate are dimmable (Switchdim). Complies with EN60598-1 and other specific standards.

LED 13W 2x19° 4000K

ВЫБРАТЬ

LED

Translucent/Anodized

КОД ПРОДУКТА

M200503

Вид светового потока



IP40

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Pad 230V Track - 14,5W
4000K - 36°
Код: M200503
Цвет: Translucent/Anodized
Материал: Aluminium, plastic
Серии: Architectural
Окружающая среда: Внутреннее
место контракта: Розничные магазины,
Музеи & Выставки


ОПТИКА

Вид светового потока: Accent Lighting

РАЗМЕРЫ

Длина: cm 8.5
Ширина: cm 1.6
Высота: cm 27
Угол наклона: 9090
Вращение: 358
Вес: kg 0.4
тест раскаленной
проводакой: 650 °

РАЗМЕРЫ



ЦВЕТ



ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED
Ватт: 12W
Световой поток (lm): 1060lm
Типология: 1
Цветовая температура (K): 4000K
Класс: A

LUMINAIR

ПРА: Electronic
integrated
Watt: 14,5W
Напряжение: 220V-240V

