

## ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

### Pad Square Ceiling - 29W 3000K - 12°



#### ДИЗАЙН:

Carlotta de Bevilacqua  
2011

#### МАТЕРИАЛЫ:

Aluminium, Polycarbonat

#### ОПИСАНИЕ:

An extension of the PAD (POËME DE L'ANGLE DROIT) concept, PAD SQUARE houses an array of 24 LEDs (26W in total) placed on the aluminium body that acts as heat dissipator. The special, patented electrical system houses the power supply within the shell, and allows a direct connection to the electrical network. A translucent cover in polycarbonate closes off the body. It acts as a support for the various lenses, ensures protection for the electrical parts and provides a diffused lighting effect. Rotation of up to 358°, tilt angle of up to 180°. 4 installation options: with adaptor for 3-circuit track, with gear plate for mounting within Algoritmo product range, wall/ceiling mounted version, or base plate for semi-recessed mounting. Complies with EN60598-1 and other specific standards.

LED 26W 2x6° 3000K

#### ВЫБРАТЬ

LED

translucent/anodized

#### КОД ПРОДУКТА

M201501

#### Вид светового потока



IP40

#### ТЕХНИЧЕСКИЕ ДАННЫЕ

##### ХАРАКТЕРИСТИКИ

Наименование продукции: Pad Square Ceiling - 29W 3000K - 12°  
Код: M201501  
Цвет: translucent/anodized  
Материал: Aluminium, Polycarbonat  
Серии: Architectural  
место контракта: Розничные магазины, Музеи & Выставки


##### ОПТИКА

Вид светового потока: Accent lighting

##### РАЗМЕРЫ

Длина: cm 16.8  
Ширина: cm 1.6  
Высота: cm 28.1  
Глубина: cm 1.6  
Угол наклона: 9090  
Вращение: 358°  
Вес: kg 1  
тест раскаленной проволокой: 650° °

##### РАЗМЕРЫ



##### ЦВЕТ



##### ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

**LED** Категория: LED  
Ватт: 24W  
Световой поток (lm): 1988lm  
Типология: 1  
Цветовая температура (K): 3000K  
Класс: A

##### LUMINAIR

Наличие трансформатора: Included (non dimmable)  
Watt: 29W  
Напряжение: 230-240V