

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Pad Square Track - 29W 4000K - 24°



ДИЗАЙН:

Carlotta de Bevilacqua
2011

МАТЕРИАЛЫ:

Extruded aluminium, translucent polycarbonate

ОПИСАНИЕ:

An extension of the PAD (POÈME DE L'ANGLE DROIT) concept, PAD SQUARE houses an array of 24 LEDs (26W in total) placed on the aluminium body that acts as heat dissipator. The special, patented electrical system houses the power supply within the shell, and allows a direct connection to the electrical network. A translucent cover in polycarbonate closes off the body. It acts as a support for the various lenses, ensures protection for the electrical parts and provides a diffused lighting effect. Rotation of up to 358°, tilt angle of up to 180°. 4 installation options: with adaptor for 3-circuit track, with gear plate for mounting within Algoritmo product range, wall/ceiling mounted version, or base plate for semi-recessed mounting. Complies with EN60598-1 and other specific standards.

LED 26W 2x12° 4000K

ВЫБРАТЬ

LED

translucent/anodized

КОД ПРОДУКТА

M201803

Вид светового потока



IP40

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции:	Pad Square Track - 29W 4000K - 24°
Код:	M201803
Цвет:	translucent/anodized
Материал:	Extruded aluminium, translucent polycarbonate
Серии:	Architectural
место контракта:	Розничные магазины, Музеи & Выставки


ОПТИКА

Вид светового потока:	Accent lighting
-----------------------	-----------------

РАЗМЕРЫ

Длина:	cm 16.8
Ширина:	cm 1.6
Высота:	cm 25.4
Глубина:	cm 1.6
Угол наклона:	9090
Вращение:	358°
Вес:	kg 0.6
тест раскаленной проволокой:	650° °

РАЗМЕРЫ



ЦВЕТ



ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

LED	Категория:	LED
	Ватт:	24W
	Световой поток (lm):	2120lm
	Типология:	1
	Цветовая температура (K):	4000K
	Класс:	A

LUMINAIR

Наличие трансформатора:	Included (non dimmable)
Watt:	29W
Напряжение:	230-240V