


ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Pad System_3000K_White

**ДИЗАЙН:**

Carlotta de Bevilacqua
2014

МАТЕРИАЛЫ:**ОПИСАНИЕ:**

Pad System is the result of a study on the theme of office lighting, which defines a new way of producing light where functional quality and comfort are the main values. With the innovative patented ALEF (Advanced Light Emitting Film) technology of LG, Pad System upsets the traditional optical approaches (based on reflectors and refractors) used in working environments, which allow to control light emission but, at the same time, result into a non-uniform appearance of the appliance's output surface. With ALEF, a patent derived from TV-screen backlighting systems, Pad System appears as a perfectly uniform luminous surface, capable to control emission over 60° beyond the appliance's ordinary one while ensuring high uniformity values, low luminance levels, and an UGR below 19, according to the provisions of UNI 12464 (luminance at 65° <3000 cd/m² – average UGR < 19). The appliance's body has a very thin aluminium edge (90x20mm), which makes Pad System one of the world's slimmest technical office lighting systems. Flexibility is ensured by the joints, which allow to obtain multiple modular configurations.

ВЫБРАТЬ**КОД ПРОДУКТА**

M3051W21

Вид светового потока

IP20

Dimmable

ТЕХНИЧЕСКИЕ ДАННЫЕ**ХАРАКТЕРИСТИКИ**

Наименование продукции: Pad System_3000K_White
Код: M3051W21
Цвет: White
Серии: Architectural
место контракта: Гостеприимство
Гостиницы,
Гостеприимство
Рестораны, Розничные
магазины, Музеи &
Выставки, Частные
резиденции

РАЗМЕРЫ**ЦВЕТ****РАЗМЕРЫ**

Длина: cm 120
Ширина: cm 19
Высота: cm 1.6

ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED
Ватт: 36W
Световой поток (lm): 3125lm
Типология: 0
Цветовая температура (K): 3000K
Класс: A

LUMINAIR

Watt: 36W

АКСЕССУАРЫ

M305220

M305320

M305420

linea - 1M. Occupa 1 indirizzo
dali M305521



Kit alimentazione per moduli in
linea - 2M. Occupa 1 indirizzo
dali M305621



Kit alimentazione per moduli in
linea e angolari - 1M+1M.
Occupa 1 indirizzo dali
M305721



Kit alimentazione per moduli in
linea e angolari - 1M+2M.
Occupa 2 indirizzi dali M305821



Kit alimentazione per moduli in
linea e angolari - 2M+2M.
Occupa 2 indirizzi dali
M305921