


## ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

### Pad System\_3000K\_Polished aluminium

**ДИЗАЙН:**

Carlotta de Bevilacqua  
2014

**МАТЕРИАЛЫ:****ОПИСАНИЕ:**

Pad System is the result of a study on the theme of office lighting, which defines a new way of producing light where functional quality and comfort are the main values. With the innovative patented ALEF (Advanced Light Emitting Film) technology of LG, Pad System upsets the traditional optical approaches (based on reflectors and refractors) used in working environments, which allow to control light emission but, at the same time, result into a non-uniform appearance of the appliance's output surface. With ALEF, a patent derived from TV-screen backlighting systems, Pad System appears as a perfectly uniform luminous surface, capable to control emission over 60° beyond the appliance's ordinary one while ensuring high uniformity values, low luminance levels, and an UGR below 19, according to the provisions of UNI 12464 (luminance at 65° <3000 cd/m<sup>2</sup> – average UGR < 19). The appliance's body has a very thin aluminium edge (90x20mm), which makes Pad System one of the world's slimmest technical office lighting systems. Flexibility is ensured by the joints, which allow to obtain multiple modular configurations.

**ВЫБРАТЬ**

LED

Polished aluminium

**КОД ПРОДУКТА**


M3051W61

**Вид светового потока**

IP20

**Dimmable****ТЕХНИЧЕСКИЕ ДАННЫЕ****ХАРАКТЕРИСТИКИ**

Наименование продукции: Pad System\_3000K\_Polished aluminium  
Код: M3051W61  
Цвет: Polished aluminium  
Серии: Architectural  
место контракта: Гостеприимство, Гостиницы, Гостеприимство, Рестораны, Розничные магазины, Музеи & Выставки, Частные резиденции

**РАЗМЕРЫ****ЦВЕТ****РАЗМЕРЫ**

Длина: cm 120  
Ширина: cm 19  
Высота: cm 1.6

**ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ**

Категория: LED  
Ватт: 36W  
Световой поток (lm): 3125lm  
Типология: 0  
Цветовая температура (K): 3000K  
Класс: A

**LUMINAIR**

Watt: 36W

**АКСЕССУАРЫ**

PadSystem\_Kit\_Terminale\_AllBrillan  
M305260

PadSystem\_GiuntoLineare\_Alimenta  
M305360

PadSystem\_Angolo90°\_AllBrillan  
M305460

Kit alimentazione per moduli in  
linea - 1M. Occupa 1 indirizzo  
dali M305521



Kit alimentazione per moduli in  
linea - 2M. Occupa 1 indirizzo  
dali M305621

Kit alimentazione per moduli in  
linea e angolari - 1M+1M.  
Occupi 1 indirizzo dali  
M305721

Kit alimentazione per moduli in  
linea e angolari - 1M+2M.  
Occupi 2 indirizzi dali M305821

Kit alimentazione per moduli in  
linea e angolari - 2M+2M.  
Occupi 2 indirizzi dali  
M305921