

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Sostituto - 4000K - 9°



ДИЗАЙН:

Ernesto Gismondi
2014

МАТЕРИАЛЫ:

ОПИСАНИЕ:

Light fixture with direct emission, with monochromatic LED light sources. Floor, wall, eaves installation. Consists of lighting unit, wiring terminal board and fixing plate. Rotation on the base +/-10°, body tilting +/-90. Positioning is maintained by means of locking dowels. EN AB47100 aluminium body and terminal board, silicone gaskets. Electronic ballast integrated in the body. Polycarbonate diffuser silicone-sealed to the lens supporting unit. Composed by 3 interchangeable optical units. IP67 connector for the electrical connection to the mains, which can be located in the base compartment and is suitable for 5-13.5mm diameter cables. LED circuits with PMMA lenses in 3 beam versions: 5°, 11,5° and elliptical 12x20°. All the screws used outside the product are in AISI 316 stainless steel. All the components in die-cast aluminium are painted with 3-stage outdoor treatment: nanotechnologies, anti-oxidizing primer, polyester paint. Technical features of the lighting fixtures in compliance with EN60598-1 and section 2-5. IP Rating IP66. Protection level from 4KV impulse overvoltage. Insulation class II. CE certification.

ВЫБРАТЬ

LED

Grey antracite

КОД ПРОДУКТА

T418410N00

Вид светового потока

IP65

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Sostituto - 4000K - 9°
Код: T418410N00
Цвет: Grey antracite
Серии: Outdoor

РАЗМЕРЫ

Длина: cm 32
Ширина: cm 6
Высота: cm 65.3
Ударопрочность: IK10
тест раскаленной проволокой: 750 °


ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED
Ватт: 105W
Световой поток (lm): 7523lm
Типология: 1
Цветовая температура (K): 4000K
Класс: A

LUMINAIR

Watt: 105W
Напряжение: 220V-240 V

РАЗМЕРЫ



ЦВЕТ

