Artemide

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Sostituto - 4000K - 24°




дизайн:

Ernesto Gismondi 2014

материалы:

ОПИСАНИЕ:

Light fixture with direct emission, with monochromatic LED light sources. Floor, wall, eaves installation. Consists of lighting unit, wiring terminal board and fixing plate. Rotation on the base +/-10°, body tilting +/-90. Positioning is maintained by means of locking dowels. EN AB47100 aluminium body and terminal board, silicone gaskets. Electronic ballast integrated in the body. Polycarbonate diffuser silicone-sealed to the lens supporting unit. Composed by 3 interchangeable optical units. IP67 connector for the electrical connection to the mains, which can be located in the base compartment and is suitable for 5-13.5mm diameter cables. LED circuits with PMMA lenses in 3 beam versions: 5°, 11,5° and elliptical 12x20°All the screws used outside the product are in AISI 316 stainless steel. All the components in die-cast aluminium are painted with 3-stage outdoor treatment: nanotechnologies, anti-oxidizing primer, polyester paint. Technical features of the lighting fixtures in compliance with EN60598-1 and section 2-5. IP Rating IP66. Protection level from 4KV impulse overvoltage. Insulation class II.



Вид светового потока



ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ Наименование продукции: Sostituto - 4000K - 24° Код: T418423N00

 Код:
 1418423N00

 Цвет:
 Grey antracite

 Серии:
 Outdoor

РАЗМЕРЫ

Длина: cm 32 Ширина: cm 6 Высота: cm 65.3 Ударопрочность: IK10 тест раскаленной 750°

ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

 Категория:
 LED

 Ватт:
 105W

 Световой поток (lm):
 7523Im

 Типология:
 1


 Цветовая температура (K):
 4000K

 Класс:
 A

LUMINAIR

 Watt:
 105W

 Напряжение:
 220V-240 V





РАЗМЕРЫ