

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Spike 17W - 10° 3000K



ДИЗАЙН:

Artemide  
2011

МАТЕРИАЛЫ:

Aluminium,transparent tempered glass.

ОПИСАНИЕ:

Light fixture with high-performance LED light sources.Wall/ceiling installation. Monochromatic version or RGB version.Body in extruded EN AW6060 T5 aluminium.Diffuser in 3mm-thick transparent tempered glass.Diffuser in 1,5mm-thick transparent polycarbonate.Stoppers in die-cast aluminium with silicone gasket.Adjustable brackets in aluminium. Electrical connection to the ballast by means of a H05RN-F (monochrome) or a 4-poles sylicon/rubber cable (RGB), with IP68 terminal board supplied with the fixture (IP65 version).24Vdc remote ballast.Painted profile with 2-stage outdoor treatment: primer, outdoor paint.Antidazzle screen in painted extruded aluminium, upon request.Optics. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 2 colour temperatures:Warm = 3000KNeutral = 4000KRGB version with red, green and blue monochromatic LEDs.IP Rating IP65. Insulation class III.Technical features of light fixtures in compliance with EN60598-1.Installation must be carried out by specialized personnel.

ВЫБРАТЬ

LED

Aluminium

КОД ПРОДУКТА

NL1707110K0

Вид светового потока



Dimmable

ТЕХНИЧЕСКИЕ ДАННЫЕ	
<div><div>ХАРАКТЕРИСТИКИ</div><div><div>Наименование продукции:</div><div>Spike 17W - 10° 3000K</div></div><div><div>Код:</div><div>NL1707110K0</div></div><div><div>Цвет:</div><div>Aluminium</div></div><div><div>Материал:</div><div>Aluminium,transparent tempered glass.</div></div><div><div>Серии:</div><div>Outdoor</div></div></div> <div><div>РАЗМЕРЫ</div><div><div>Длина:</div><div>cm 50</div></div><div><div>Ширина:</div><div>cm 4.5</div></div><div><div>Высота:</div><div>cm 4</div></div><div><div>Форма отверстия:</div><div>Прямоугольная форма</div></div><div><div>Вес:</div><div>kg 0.8</div></div></div> <div><div>ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ</div><div><div>Категория:</div><div>LED</div></div><div><div>Ватт:</div><div>17W</div></div><div><div>Световой поток (lm):</div><div>550lm</div></div><div><div>Типология:</div><div>1</div></div><div><div>Цветовая температура (K):</div><div>3000K</div></div><div><div>Класс:</div><div>A</div></div><div><div>Напряжение:</div><div>24 Vdc</div></div></div> <div><div>LUMINAIR</div><div><div>ПРА:</div><div>Remote electronic</div></div><div><div>Watt:</div><div>17W</div></div><div><div>Напряжение:</div><div>24Vdc</div></div></div>	
<div><div>РАЗМЕРЫ</div><div></div></div> <div><div>ЦВЕТ</div><div></div></div>	

NO  
IMAGE  
AVAILABLE

NO  
IMAGE  
AVAILABLE

ALIMENT. 19,2W 24Vdc (indip.)  
NL19040

ALIMENT. 70W 24Vdc (INDIP.)  
NL8711