

## ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

### Spike 34W - 10° 3000K



#### ДИЗАЙН:

Artemide  
2011

#### МАТЕРИАЛЫ:

Aluminium, transparent tempered glass.

#### ОПИСАНИЕ:

Light fixture with high-performance LED light sources. Wall/ceiling installation. Monochromatic version or RGB version. Body in extruded EN AW6060 T5 aluminium. Diffuser in 3mm-thick transparent tempered glass. Diffuser in 1,5mm-thick transparent polycarbonate. Stoppers in die-cast aluminium with silicone gasket. Adjustable brackets in aluminium. Electrical connection to the ballast by means of a H05RN-F (monochrome) or a 4-poles sylicon/rubber cable (RGB), with IP68 terminal board supplied with the fixture (IP65 version). 24Vdc remote ballast. Painted profile with 2-stage outdoor treatment: primer, outdoor paint. Antidazzle screen in painted extruded aluminium, upon request. Optics. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 2 colour temperatures: Warm = 3000K Neutral = 4000K RGB version with red, green and blue monochromatic LEDs. IP Rating IP65. Insulation class III. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel.

#### ВЫБРАТЬ

LED

Aluminium

#### КОД ПРОДУКТА

NL1707210K0

#### Вид светового потока

IP40



#### ТЕХНИЧЕСКИЕ ДАННЫЕ

##### ХАРАКТЕРИСТИКИ

Наименование продукции: Spike 34W - 10° 3000K  
Код: NL1707210K0  
Цвет: Aluminium  
Материал: Aluminium, transparent tempered glass.  
Серии: Outdoor

##### РАЗМЕРЫ

Длина: cm 100  
Ширина: cm 4.5  
Высота: cm 4  
Форма отверстия: Прямоугольная форма  
Вес: kg 1.3


##### ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED  
Ватт: 34 W  
Световой поток (lm): 4000 lm  
Типология: 1  
Цветовая температура (K): 3000 K  
Класс: A

##### LUMINAIR

ПРА: Remote electronic  
Watt: 34W  
Напряжение: 24Vdc

##### РАЗМЕРЫ



##### ЦВЕТ



#### АКСЕССУАРЫ



ALIMENT. 19,2W 24Vdc (indip.)  
NL19040

ALIMENT. 70W 24Vdc (INDIP.)  
NL8711