

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Spike 34W - 25° 3000K



ДИЗАЙН:

Artemide
2011

МАТЕРИАЛЫ:

Aluminium, transparent tempered glass.

ОПИСАНИЕ:

Light fixture with high-performance LED light sources. Wall/ceiling installation. Monochromatic version or RGB version. Body in extruded EN AW6060 T5 aluminium. Diffuser in 3mm-thick transparent tempered glass. Diffuser in 1,5mm-thick transparent polycarbonate. Stoppers in die-cast aluminium with silicone gasket. Adjustable brackets in aluminium. Electrical connection to the ballast by means of a H05RN-F (monochrome) or a 4-poles sylicon/rubber cable (RGB), with IP68 terminal board supplied with the fixture (IP65 version). 24Vdc remote ballast. Painted profile with 2-stage outdoor treatment: primer, outdoor paint. Antidazzle screen in painted extruded aluminium, upon request. Optics. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 2 colour temperatures: Warm = 3000K Neutral = 4000K RGB version with red, green and blue monochromatic LEDs. IP Rating IP65. Insulation class III. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel.

ВЫБРАТЬ

LED

Aluminium

КОД ПРОДУКТА

NL1707225K0

Вид светового потока

IP40  

ТЕХНИЧЕСКИЕ ДАННЫЕ


ХАРАКТЕРИСТИКИ

Наименование продукции: Spike 34W - 25° 3000K
Код: NL1707225K0
Цвет: Aluminium
Материал: Aluminium, transparent tempered glass.
Серии: Outdoor

РАЗМЕРЫ

Длина: cm 100
Ширина: cm 4.5
Высота: cm 4
Форма отверстия: Прямоугольная форма
Вес: kg 1.3

РАЗМЕРЫ



ЦВЕТ



ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED
Ватт: 34 W
Световой поток (lm): 4000 lm
Типология: 1
Цветовая температура (K): 3000 K
Класс: A

LUMINAIR

ПРА: Remote electronic
Watt: 34W
Напряжение: 24Vdc

АКСЕССУАРЫ

NO
IMAGE
AVAILABLE

NO
IMAGE
AVAILABLE

ALIMENT. 19,2W 24Vdc (indip.)
NL19040

ALIMENT. 70W 24Vdc (INDIP.)
NL8711