

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Spike 34W - 14°x34° 4000K



ДИЗАЙН:

Artemide
2011

МАТЕРИАЛЫ:

Aluminium, transparent tempered glass.

ОПИСАНИЕ:

Light fixture with high-performance LED light sources. Wall/ceiling installation. Monochromatic version or RGB version. Body in extruded EN AW6060 T5 aluminium. Diffuser in 3mm-thick transparent tempered glass. Diffuser in 1,5mm-thick transparent polycarbonate. Stoppers in die-cast aluminium with silicone gasket. Adjustable brackets in aluminium. Electrical connection to the ballast by means of a H05RN-F (monochrome) or a 4-poles sylicon/rubber cable (RGB), with IP68 terminal board supplied with the fixture (IP65 version). 24Vdc remote ballast. Painted profile with 2-stage outdoor treatment: primer, outdoor paint. Antidazzle screen in painted extruded aluminium, upon request. Optics. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 2 colour temperatures: Warm = 3000K Neutral = 4000K RGB version with red, green and blue monochromatic LEDs. IP Rating IP65. Insulation class III. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel.

ВЫБРАТЬ

LED

Aluminium

КОД ПРОДУКТА

NL17072ELW0

Вид светового потока

IP40



ТЕХНИЧЕСКИЕ ДАННЫЕ


ХАРАКТЕРИСТИКИ

Наименование продукции:	Spike 34W - 14°x34° 4000K
Код:	NL17072ELW0
Цвет:	Aluminium
Материал:	Aluminium, transparent tempered glass.
Серии:	Outdoor

РАЗМЕРЫ

Длина:	cm 100
Ширина:	cm 4.5
Высота:	cm 4
Форма отверстия:	Прямоугольная форма
Вес:	kg 1.3

РАЗМЕРЫ



ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория:	LED
Ватт:	34 W
Световой поток (lm):	1000 lm
Типология:	1
Цветовая температура (K):	4000 K
Класс:	A

ЦВЕТ



LUMINAIR

ПРА:	Remote electronic
Watt:	34W
Напряжение:	24Vdc

АКСЕССУАРЫ

NO
IMAGE
AVAILABLE

NO
IMAGE
AVAILABLE

ALIMENT. 19,2W 24Vdc (indip.)
NL19040

ALIMENT. 70W 24Vdc (INDIP.)
NL8711