

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

SurfSystemLed_DALI_65W_3000K_5474lm_Silver

**ДИЗАЙН:**

Neil Poulton
1998

МАТЕРИАЛЫ:

Extruded Aluminium

ОПИСАНИЕ:

A valid alternative to fluorescent modules for general lighting solutions of the tertiary buildings, school premises, public or industrial spaces, and circulation areas, Surf System Led is a more than attractive option easily interchangeable with Surf System fluorescent modules of 1193mm (2x54W T16) or 1493mm (2x80W) long. The same lighting level is obtained with up to 50 % less energy consumed and an exceptional luminaire efficiency of up to 100lm/W. A targeted range is available: two lengths of modules (1193 and 1493mm), four luminous flux options and two colour temperatures (3000K/5350lm-7000lm and 4000K/5450lm-7300lm) and three modes of electronic lighting management (non dimmable, dimmable Dali and Interactive-Dali System). Surf System Led is available in the same dimensions and is using the same finishing and fixing components like Surf System T16, guaranteeing perfect interchangeability with the fluorescent version. 1193 mm long module: Total luminous flux of luminaire: 5350 lm (3000 K) - 5450 lm (4000 K) Luminaire efficiency: 99 lm/W (3000 K) - 101 lm/W (4000 K) Light distribution: 100% indirect Total power of luminaire: 54W

ВЫБРАТЬ**КОД ПРОДУКТА**

M095191


Вид светового потока

IP20

Dimmable

ТЕХНИЧЕСКИЕ ДАННЫЕ**ХАРАКТЕРИСТИКИ**

Наименование продукции: SurfSystemLed_DALI_65W_3000K_5474lm_Silver
Код: M095191
Цвет: White
Материал: Extruded Aluminium
Серии: Architectural
Окружающая среда: Внутреннее
место контракта: Гостеприимство Гостиницы, Гостеприимство Рестораны, Розничные магазины, Офисы, Музеи & Выставки

РАЗМЕРЫ**ЦВЕТ****РАЗМЕРЫ**

Длина: cm 119
Ширина: cm 18
Высота: cm 3,2
Вес: kg 5,1
тест раскаленной проволокой: 960 °

ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED
Ватт: 57W
Световой поток (lm): 6630lm
Типология: 1
Цветовая температура (K): 3000K
Класс: A

LUMINAIR

Watt: 65W
Напряжение: 220V-240V



SURF ATTACCO A PARETE
BCO M090820



SURF GIUNTO 90° BCO
M090320



SURF TERMINALE BCO
M090220



SURF ELEMENT DE
JONCTION T BLC M090420



SURF BASETTA SOSP.BCO
M090620



SURF ELEMENT DE JONCTION
+ BLC M090520



SURF BASETTA
SOSP.ALIM.BCO M090720



SURF SOSPENS. ALIM.5 POLI
BCO M091820



SURF ATTACCO A PTE
ALIM.BCO M090920



INTERACTIVE-DALI remote
control. M104900



INTERACTIVE-DALI kit Ø86mm,
white, recessed. Can be
connected to a max. 11 DALI
dimnable units. Is operated
through INTERACTIVE-DALI
remote control or external push
button. M074030



Extension movement detector
white, recessed. To be used
when the area to be covered is
bigger than 6,00x5,00m by
height 2,50m. To be connected
to one of the outputs of the
INTERACTIVE-DALI controller.
No extra mains connection
required. M074130