

## ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

### Surf System Led - Dimmable DALI - 4000K - Grey

**ДИЗАЙН:**

Neil Poulton  
1998

**МАТЕРИАЛЫ:**

Extruded Aluminium

**ОПИСАНИЕ:**

A valid alternative to fluorescent modules for general lighting solutions of the tertiary buildings, school premises, public or industrial spaces, and circulation areas, Surf System Led is a more than attractive option easily interchangeable with Surf System fluorescent modules of 1193mm (2x54W T16) or 1493mm (2x80W) long. The same lighting level is obtained with up to 50 % less energy consumed and an exceptional luminaire efficiency of up to 100lm/W. A targeted range is available: two lengths of modules (1193 and 1493mm), four luminous flux options and two colour temperatures (3000K/5350lm-7000lm and 4000K/5450lm-7300lm) and three modes of electronic lighting management (non dimmable, dimmable Dali and Interactive-Dali System). Surf System Led is available in the same dimensions and is using the same finishing and fixing components like Surf System T16, guaranteeing perfect interchangeability with the fluorescent version. 1193 mm long module: Total luminous flux of luminaire: 5350 lm (3000 K) - 5450 lm (4000 K) Luminaire efficiency: 99 lm/W (3000 K) - 101 lm/W (4000 K) Light distribution: 100% indirect Total power of luminaire: 54W

**ВЫБРАТЬ**

LED

Grey

**КОД ПРОДУКТА**

M095291


**Вид светового потока**

IP20

Dimmable

**ТЕХНИЧЕСКИЕ ДАННЫЕ****ХАРАКТЕРИСТИКИ**

Наименование продукции: Surf System Led - Dimmable DALI - 4000K - Grey  
Код: M095291  
Цвет: Grey  
Материал: Extruded Aluminium  
Серии: Architectural  
Окружающая среда: Внутреннее место контракта: Гостеприимство, Гостиницы, Гостеприимство, Рестораны, Розничные магазины, Офисы

**РАЗМЕРЫ****ЦВЕТ****ОПТИКА**

Вид светового потока: Indirect

**РАЗМЕРЫ**

Длина: cm 119  
Ширина: cm 18  
Высота: cm 3.2  
Вес: kg 5.1  
тест раскаленной проволокой: 960 °

**ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ**

Категория: LED  
Ватт: 58W  
Световой поток (lm): 7850lm  
Типология: 1  
Цветовая температура (K): 4000K  
Класс: A

**LUMINAIR**

Watt: 65W  
Напряжение: 220V-240V


AKCECCУAPЫ



SURF ATTACCO A PARETE  
BCO M090820



SURF GIUNTO 90° BCO  
M090320



SURF TERMINALE BCO  
M090220



SURF ELEMENT DE  
JONCTION T BLC M090420



SURF BASETTA SOSP.BCO  
M090620



SURF ELEMENT DE JONCTION  
+ BLC M090520



SURF BASETTA  
SOSP.ALIM.BCO M090720



SURF SOSPENS. ALIM.5 POLI  
BCO M091820



SURF ATTACCO A PTE  
ALIM.BCO M090920



INTERACTIVE-DALI remote  
control. M104900



INTERACTIVE-DALI kit Ø86mm,  
white, recessed. Can be  
connected to a max. 11 DALI  
dimmable units. Is operated  
through INTERACTIVE-DALI  
remote control or external push  
button. M074030



Extension movement detector  
white, recessed. To be used  
when the area to be covered is  
bigger than 6,00x5,00m by  
height 2,50m. To be connected  
to one of the outputs of the  
INTERACTIVE-DALI controller.  
No extra mains connection  
required. M074130