

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Zeno Up 3 - 24° 3000K - Silver



ДИЗАЙН:

Jan Van Lierde
2011

МАТЕРИАЛЫ:

ОПИСАНИЕ:

Light fixture with high-performance LED light sources. Ceiling installation. Low recessed depth. Consist of body, frame, black silkscreened tempered glass, fixing springs. Body in EN AB44100 aluminium, silicone gaskets. Frame in aluminium. Black silkscreened tempered glass, 8mm-thick. Fixing springs in harmonic iron. Power connection to the mains by means of a H05RN-r cable and IP68 electrical terminal board, supplied with the fixture (IP65). Glass surface temperature lower than 40°C. Fixed optics. PMMA lenses in 2 different versions of beams. White monochromatic LEDs available in 2 colour temperatures: Warm = 3000K Neutral = 4000K Painted die-cast aluminium with 3-stage outdoor treatment: nanotechnologies, antioxidant primer, polyester paint. Technical features of light fixtures in compliance with EN60598-1 and part 2-13. IP Rating IP65 e IP40. Insulation class III. Installation must be carried out by specialised personnel. Carefully follow the instructions

ВЫБРАТЬ

LED

Silver

КОД ПРОДУКТА

NL1708525K002

Вид светового потока

65

ТЕХНИЧЕСКИЕ ДАННЫЕ


ХАРАКТЕРИСТИКИ

Наименование продукции: Zeno Up 3 - 24° 3000K - Silver
 Код: NL1708525K002
 Цвет: Silver
 Серии: Architectural

РАЗМЕРЫ

Длина: cm 6.5
 Ширина: cm 6.5
 Длина отверстия: cm 5.6
 Ширина отверстия: cm 5.2
 Глубина встройки: cm 4.6

РАЗМЕРЫ



ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED
 Ватт: 5W
 Световой поток (lm): 384lm
 Типология: 1
 Цветовая температура (K): 3000K
 Класс: A

ЦВЕТ



LUMINAIR

Watt: 5W

АКСЕССУАРЫ



ALIMENT. 13,5W 500mA IP67
NL19046

ALIMENT. 8W 500mA (INDIP.)
NL10941

