

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Zeno Up 4 - 30° 3000K - White

**ДИЗАЙН:**

Jan Van Lierde
2011

МАТЕРИАЛЫ:**ОПИСАНИЕ:**

Light fixture with high-performance LED light sources. Ceiling installation. Low recessed depth. Consist of body, frame, black silkscreened tempered glass, fixing springs. Body in EN AB44100 aluminium, silicone gaskets. Frame in aluminium. Black silkscreened tempered glass, 8mm-thick. Fixing springs in harmonic iron. Power connection to the mains by means of a H05RN-r cable and IP68 electrical terminal board, supplied with the fixture (IP65). Glass surface temperature lower than 40°C. Fixed optics. PMMA lenses in 2 different versions of beams. White monochromatic LEDs available in 2 colour temperatures: Warm = 3000K Neutral = 4000K Painted die-cast aluminium with 3-stage outdoor treatment: nanotechnologies, antioxydant primer, polyester paint. Technical features of light fixtures in compliance with EN60598-1 and part 2-13. IP Rating IP65 e IP40. Insulation class III. Installation must be carried out by specialised personnel. Carefully follow the instructions

ВЫБРАТЬ**КОД ПРОДУКТА**

NL1708725K006

Вид светового потока


40

ТЕХНИЧЕСКИЕ ДАННЫЕ**ХАРАКТЕРИСТИКИ**

Наименование продукции: Zeno Up 4 - 30° 3000K - White
Код: NL1708725K006
Цвет: White
Серии: Architectural

РАЗМЕРЫ

Длина: cm 9
Ширина: cm 9
Длина отверстия: cm 7.9
Ширина отверстия: cm 7.9
Глубина встройки: cm 5

РАЗМЕРЫ**ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ**

Категория: LED
Ватт: 6,5W
Световой поток (lm): 520lm
Типология: 1
Цветовая температура (K): 3000K
Класс: A

ЦВЕТ**LUMINAIR**

Watt: 6,5W

АКСЕССУАРЫ

ALIMENT. 13,5W 500mA IP67
NL19046

ALIMENT. 8W 500mA (INDIP.)
NL10941

