

serie/series

mira 65

LED

powered by
Seoul® Semiconductor Z5M



simmetrico
symmetric
symétriques
simétrico
symmetrisch



asimmetrico
asymmetric
asymétriques
asimétrico
asymmetrisch

example code:

art.	LED		anodized
5321	LS5	N	inx

art.
5321
5322

design Ufficio Tecnico Landa



corpo alluminio estruso
anodizzato

body in extruded anodized
aluminium

corps en aluminium extrudé
anodisé

cuerpo en aluminio
extrusionado y anodizado

Körper aus eloxiertem
fließgepresst Aluminium


diffusore vetro trasparente
e opale

diffuser glass transparent
and opal

diffuser verre transparent
et opale

difusor vidrio transparente
y ópalo

Diffuser Glas klar und opal




FOR TECHNICAL DETAILS VISIT
www.landa.it

IP67



5321



codeLS5



5321




codeLL5



5321



codeL5



art.	LUX 1mt	art.	LUX 1mt	art.	LUX 1mt	W	V	Type	⚡	Ra
5321LS5N3740	10°	5321LL5N 700	40°	5321L5N 124		5	24	4000K 480LM	80	
5321LS5H3740		5321LL5H 700		5321L5H 124				3000K 480LM	80	

ELECTRIFICATION

LED

dettagli / details / details
detales / details:
p.A54 - A55

Energy efficiency classes

Trasformer available:

cod. 0409BT014 to connect up to 2 pieces – GE LIGHTING IP67 24V c.c. 12W
cod. 0409BT015 to connect up to 4 pieces – GE LIGHTING IP67 24V c.c. 25W

Trasformer on request:

cod. 0409BT016 to connect up to 16 pieces – GE LIGHTING IP67 24V c.c. 100W

A++ ÷ A

mira 65 (24V)

Projectors
NEW
Recessed

Contemporary

Traditional



RECESSED

33


Thanks to MP Illumination - GR



5322



codeL5



....brz




....inx

art.		W	V	Type	⚡	Ra
5322 L5N	○	5	24	4000K 480LM	80	
5322 L5H	○	5	24	3000K 480LM	80	



brz



inx

Accessories on request:



code 0404M009
Single connection IP68

