

8 800 301-72-50  
<http://lampshopping.ru>


# COCOZ ROUND

## 1.0 LED111

LED 13W | 220-240V | 50-60Hz  
 AC-COB 3-step | phase-cut dim  
 aluminium | steel powder coated

CE 1.06 kg □ 960° IP20 (0,3) A 38°

□ 152  
 ∩ 25°/25° □ 170  
 ↻ 365° □ 2-25




## 1.0 QR111

QR111 max. 75W | G53 | 12V  
 excl. transformer  
 aluminium | steel powder coated

CE 0.78 kg TE 960° IP20 (0,9)

□ 152  
 ∩ 25°/25° □ 170  
 ↻ 365° □ 2-25




## 1.0 HIR111

HIR-CE111 35/70W | GX8.5  
 220-240VAC | 50-60Hz | excl. ballast  
 aluminium | steel powder coated

CE 0.78 kg 960° IP20 (0,7)

□ 152  
 ∩ 25°/25° □ 170  
 ↻ 365° □ 2-25



119168J\_

119168U\_



119130J0

119130U0



1191H0J0

1191H0U0

**LIGHT COLOUR**  
 2700K | >80CRI | 640lm 2  
 3000K | >80CRI | 680lm 4

**ALWAYS USE**  
 transformer  
 12V | 60W 90221902  
 12V | 105W 90221903

**ALWAYS USE**  
 electronic ballast  
 35W 90219901  
 70W 90219902





# COCOZ SQUARE



## 1.0 LED111


LED 13W | 220-240V | 50-60Hz  
AC-COB 3-step | phase-cut dim  
aluminium | steel powder coated

CE 1.15kg □ 960° IP20 (0,3) P

□ 145x145

∩ 25°/25° ∩ 180

↻ 365° ▨ 2-25



## 1.0 QR111


QR111 max. 75W | G53 | 12V  
excl. transformer  
aluminium | steel powder coated

CE 0.87kg TE 960° IP20 (0,9)

□ 145x145

∩ 25°/25° ∩ 180

↻ 365° ▨ 2-25



## 1.0 HIR111


HIR-CE111 35/70W | GX8.5  
220-240VAC | 50-60Hz | excl. ballast  
aluminium | steel powder coated

CE 0.87kg 960° IP20 (0,7)

□ 145x145

∩ 25°/25° ∩ 180

↻ 365° ▨ 2-25



LIGHT COLOUR	
2700K   >80CRI   640lm	2
3000K   >80CRI   680lm	4

ALWAYS USE	
transformer 12V   60W	90221902
12V   105W	90221903

ALWAYS USE	
electronic ballast 35W	90219901
70W	90219902

