

8 800 301-72-50
<http://lampshopping.ru>


OBOQ ROUND

1.0 LED111

LED 13W | 220-240V | 50-60Hz
 AC-COB 3-step | phase-cut dim
 aluminium | steel powder coated

CE 0.98 kg □ 960° IP20 (0,3) A 38°

□ 140
 ∪ 25°/25° 150
 ↻ 365° 2-25




1.0 QR111

QR111 max. 75W | G53 | 12V
 excl. transformer
 aluminium | steel powder coated

CE 0.70 kg TE 960° IP20 (0,9)

□ 140
 ∪ 25°/25° 150
 ↻ 365° 2-25




1.0 HIR111

HIR-CE111 35/70W | GX8.5
 220-240VAC | 50-60Hz | excl. ballast
 aluminium | steel powder coated

CE 0.70 kg 960° IP20 (0,7)

□ 140
 ∪ 25°/25° 165
 ↻ 365° 2-25



	120168J_
	120168E_
	120168K_

	120130J0
	120130E0
	120130K0

	1201H0J0
	1201H0E0
	1201H0K0

LIGHT COLOUR	
2700K >80CRI 640lm	2
3000K >80CRI 680lm	4

ALWAYS USE	
transformer	
12V 60W	90221902
12V 105W	90221903

ALWAYS USE	
electronic ballast	
35W	90219901
70W	90219902



OBOOQ SQUARE

1.0 LED111


LED 13W | 220-240V | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium | steel powder coated

CE 1.02kg □ 960° IP20 $\approx 0,3$ A 38°

□ 138x138

∩ 25°/25° ≈ 150

↻ 365° $\approx 2-25$



1.0 QR111


QR111 max. 75W | G53 | 12V
excl. transformer
aluminium | steel powder coated

CE 0.84kg TE 960° IP20 $\approx 0,9$

□ 138x138

∩ 25°/25° ≈ 150

↻ 365° $\approx 2-25$



1.0 HIR111




HIR-CE111 35/70W | GX8.5
220-240VAC | 50-60Hz | excl. ballast
aluminium | steel powder coated

CE 0.84kg 960° IP20 $\approx 0,7$

□ 138x138

∩ 25°/25° ≈ 165

↻ 365° $\approx 2-25$



LIGHT COLOUR
2700K | >80CRI | 640lm **2**
3000K | >80CRI | 680lm **4**

ALWAYS USE
transformer
12V | 60W **90221902**
12V | 105W **90221903**

ALWAYS USE
electronic ballast
35W **90219901**
70W **90219902**

