



1.0 LED


LED 7/10W | 350-500mA
 COB 3-step | excl. power supply
 aluminium powder coated

CE 0.26kg TE 960° IP20 (±0,3)

74x78

35°/35° 95

355° 2-18



1.0 PAR16


PAR16 max. 50W | GU10
 220-240VAC | 50-60Hz
 aluminium powder coated

CE 0.24kg 960° IP20 (±0,9)

74x78

35°/35° 120

355° 2-18



2.0 LED


2xLED 7/10W | 350-500mA
 COB 3-step | excl. power supply
 aluminium powder coated

CE 0.48kg TE 960° IP20 (±0,3)

74x148

35°/35° 95

355° 2-18



2.0 PAR16


2xPAR16 max. 50W | GU10
 220-240VAC | 50-60Hz
 aluminium powder coated

CE 0.44kg 960° IP20 (±0,9)

74x148

35°/35° 120

355° 2-18



LIGHT COLOUR

2200K | >80CRI | 315-465lm | 15Vf **1**
 2700K | >90CRI | 420-590lm | 18Vf **3**
 3000K | >90CRI | 470-640lm | 18Vf **5**

LIGHT COLOUR

2200K | >80CRI | 2x315-465lm | 15Vf **1**
 2700K | >90CRI | 2x420-590lm | 18Vf **3**
 3000K | >90CRI | 2x470-640lm | 18Vf **5**

ALWAYS USE

power supply
 350mA | 10W **90213402**
 500mA | 10W **90214403**

power supply phase-cut dim
 500mA | 15W **90224501**

more power supplies on page 490

OPTIONAL

PAR16 LED GU10 6W phase-cut dim
 2700K 390lm **901228W2**
 3000K 410lm **901228W4**

PAR16 LED GU10 7W ambient white dim
 1800-3000K **901229S9**

OPTIONAL

plaster kit **90017104**

ALWAYS USE

power supply
 350mA | 10W **90213402**
 500mA | 10W **90214403**

power supply phase-cut dim
 500mA | 15W **90224501**

more power supplies on page 490

OPTIONAL

plaster kit **90017105**

OPTIONAL

PAR16 LED GU10 6W phase-cut dim
 2700K 390lm **901228W2**
 3000K 410lm **901228W4**

PAR16 LED GU10 7W ambient white dim
 1800-3000K **901229S9**

OPTIONAL

plaster kit **90017105**



PLANO



1.0 LED111


LED 13W | 220-240V | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium powder coated

CE 0.65kg □ TE 960° IP20 $\approx 0,3$

□ 141x145

∩ 35°/35° ≈ 90

↻ 355° $\approx 2-18$



1.0 ES111


ES111 max. 75W | GU10
220-240V | VAC | 50-60Hz
aluminium powder coated

CE 0.41kg □ 960° IP20 $\approx 0,9$

□ 141x145

∩ 35°/35° ≈ 145

↻ 355° $\approx 2-18$



1.0 QR111


QR111 max. 75W | G53 | 12V
excl. transformer
aluminium powder coated

CE 0.41kg □ TE 960° IP20 $\approx 0,9$

□ 141x145

∩ 35°/35° ≈ 90

↻ 355° $\approx 2-18$



LIGHT COLOUR	
2700K >80CRI 640lm	2
3000K >80CRI 680lm	4

OPTIONAL
plaster kit 90017106

OPTIONAL	
ES111 LED GU10 13W phase-cut dim 2700K 530lm	901528S2
3000K 540lm	901528S4

OPTIONAL
plaster kit 90017106

ALWAYS USE	
transformer 12V 60W	90221902
12V 105W	90221903

OPTIONAL
plaster kit 90017106