



1.0 LED


LED 7/10W | 350-500mA
 COB 3-step | excl. power supply

CE 0.36 kg 960° IP20 0,3 Λ36°

102

35°/35° 90

355° 4-40



1.0 MR16

QR-CBC51 max. 50W | GU5.3
 12V excl. transformer

CE 0.30 kg 960° IP20 0,9

102

35°/35° 75

355° 4-40



1.0 PAR16


PAR16 max. 50W | GU10
 220-240VAC | 50-60Hz

CE 0.34 kg 960° IP20 0,9

102

35°/35° 100

355° 4-40



2200K | >80CRI | 315-465lm | 15Vf

	111161W1
	111161B1

2700K | >90CRI | 420-590lm | 18Vf

	111161W3
	111161B3

3000K | >90CRI | 470-640lm | 18Vf

	111161W5
	111161B5

ALWAYS USE
 power supply
 350mA | 10W **90213402**

500mA | 10W **90214403**

power supply phase-cut dim
 500mA | 15W **90224501**

more power supplies on page 474

	11110W0
	11110S0
	11110B0

ALWAYS USE
 transformer
 12V | 60W **90221902**

12V | 105W **90221903**

	111120W0
	111120S0
	111120B0

OPTIONAL
 PAR16 LED GU10 6W phase-cut dim
 2700K 390lm **901228W2**

3000K 410lm **901228W4**

PAR16 LED GU10 7W ambient white dim
 1800-3000K **901229S9**





2.0 LED


2xLED 7/10W | 350-500mA
COB 3-step | excl. power supply

CE 0.73kg 960° IP20 0,3 A36°

102x210

35°/35° 90

355° 4-40



2.0 PAR16

2xPAR16 max. 50W | GU10
220-240VAC | 50-60Hz

CE 0.69kg 960° IP20 0,9

102x210

35°/35° 100

355° 4-40



2200K | >80CRI | 2x315-465lm | 15Vf

111261W1

111261B1

2700K | >90CRI | 2x420-590lm | 18Vf

111261W3

111261B3

3000K | >90CRI | 2x470-640lm | 18Vf

111261W5

111261B5

111220W0

111220B0

OPTIONAL

PAR16 LED GU10 6W phase-cut dim
2700K 390lm

901228W2

3000K 410lm

901228W4

PAR16 LED GU10 7W ambient white dim
1800-3000K

901229S9

ALWAYS USE

power supply
350mA | 10W

90213402

500mA | 10W

90214403

power supply phase-cut dim

500mA | 15W

90224501

more power supplies on page 474



RON

3.0 LED


3xLED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply

CE 1.08kg 96° IP20 0,3 P A36°

102x320

35°/35° 90

355° 4-40



3.0 PAR16


3xPAR16 max. 50W | GU10
220-240VAC | 50-60Hz

CE 1.02kg 96° IP20 0,9 P

102x320

35°/35° 100

355° 4-40



2700K | >90CRI | 3x420-590lm

111361W3

111361B3

3000K | >90CRI | 3x470-640lm

111361W5

111361B5

ALWAYS USE

power supply
350mA | 10W 90213402

500mA | 10W 90214403

power supply phase-cut dim
500mA | 15W 90224501

more power supplies on page 474

111320W0

111320B0

OPTIONAL

PAR16 LED GU10 6W phase-cut dim
2700K 390lm 901228W2

3000K 410lm 901228W4

PAR16 LED GU10 7W ambient white dim
1800-3000K 901229S9

