



1.0 LED

LED 7/10W | 350-500mA
 COB 3-step | excl. power supply
 aluminium powder coated

CE 0.34 kg | 960° IP20 | 0,3 | 36°

102

35°/35° 90

355° 4-40



1.0 MR16


QR-CBC51 max. 50W | GU5.3 | 12V
 excl. transformer
 aluminium powder coated

CE 0.28 kg | 960° IP20 | 0,9

102

35°/35° 75

355° 4-40



1.0 PAR16


PAR16 max. 50W | GU10
 220-240VAC | 50-60Hz
 aluminium powder coated

CE 0.32 kg | 960° IP20 | 0,9

102

35°/35° 100

355° 4-40



	110161W
	110161B

LIGHT COLOUR

2200K >80CRI 315-465lm 15Vf	1
2700K >90CRI 420-590lm 18Vf	3
3000K >90CRI 470-640lm 18Vf	5

ALWAYS USE

power supply 350mA 10W	90213402
500mA 10W	90214403
power supply phase-cut dim 500mA 15W	90224501

more power supplies on page 490

	110110W0
	110110S0
	110110B0

ALWAYS USE

transformer 12V 60W	90221902
12V 105W	90221903

	110120W0
	110120S0
	110120B0

OPTIONAL

PAR16 LED GU10 6W phase-cut dim 2700K 390lm	901228W2
3000K 410lm	901228W4
PAR16 LED GU10 7W ambient white dim 1800-3000K	901229S9

