

## ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

### Cefiso 14 - 34°x6° 4000K Light grey



#### ДИЗАЙН:

Alessandro Pedretti  
2011

#### МАТЕРИАЛЫ:

Painted aluminium, tempered glass

#### ОПИСАНИЕ:

Light fixture with adjustable direct emission, with high-performance LED light sources. Floor, wall and eaves installation. 2 sizes: Cefiso 14, Cefiso 20. Available in two finishes: grey-white and anthracite grey painted. Consist of adjustable lighting unit and terminal board. Rotation on the base +/-180°, body tilting +/-90° by means of a graduated metal ring allowing an accurate adjustment. Positioning is maintained by means of locking dowels. Body and terminal board in EN AB44100 aluminium, silicone gaskets. Electronic ballast integrated in the body. Silkscreened tempered glass siliconed flush with the body to avoid backwater. Wiring to be carried out inside the terminal board by piercing an IP65 grommet suitable for cables with a diameter of 8-13 mm. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 3 colour temperatures: Warm = 3000K Neutral = 4000K Screws in AISI 316 stainless steel. Painted die-cast aluminium with 3-stage outdoor treatment: nanotechnologies, antioxidant primer, polyester paint. Technical features of light fixtures in compliance with EN60598-1 and part 2-5. IP Rating IP65. ENEC approved. Insulation class I.

#### ВЫБРАТЬ

LED

Light grey

#### КОД ПРОДУКТА

T4180ELN00

#### Вид светового потока



IP65




#### ТЕХНИЧЕСКИЕ ДАННЫЕ

##### ХАРАКТЕРИСТИКИ

Наименование продукции: Cefiso 14 - 34°x6° 4000K  
Light grey  
Код: T4180ELN00  
Цвет: Light grey  
Материал: Painted aluminium,  
tempered glass  
Серии: Outdoor  
Окружающая среда: Уличное  
место контракта: Фасады зданий

##### РАЗМЕРЫ



##### РАЗМЕРЫ

Длина: cm 13.6  
Ширина: cm 13.6  
Высота: cm 31.3  
Ударопрочность:  
тест раскаленной  
проводами: IK10  
NA °

##### ЦВЕТ



##### ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED  
Ватт: 22W  
Световой поток (lm): 1323lm  
Количество: 1 x 9  
Типология: 1  
Цветовая температура (K): 4000K  
Класс: A

##### LUMINAIR

Watt: 22W  
Напряжение: 220V-240V



Red dot design award 2012