# ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

## Dedalo - IP65 - 48W 3800K

**ДИЗАЙН:**

Artemide
2013

**МАТЕРИАЛЫ:**

**ОПИСАНИЕ:**

Light fixture with high-performance LED light sources. Ceiling, wall or floor installation. Flexible profile. Flexible UV-resistant polyurethane resin rim. Accurate led selection equal to 3 Step MacAdam, ensuring colour consistency. 3M adhesive film to fix the product, supplied with the fixture. Remote driver. Electrical connection to the driver by means of H05RN-F (IP65) or FEP-FEP cable (IP40), and appropriate terminal board, provided with the fixture. White monochromatic LEDs available in 2 colour temperatures: Warm = 3200K Neutral = 3800K RGB Full colour LED. IP Rating IP65 or IP40. Insulation class III. Operating temperature -20°C / +40°C. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions.

ВЫБРАТЬ

LED

КОД ПРОДУКТА

NL17034VTW1

**Вид светового потока**

IP65

### ТЕХНИЧЕСКИЕ ДАННЫЕ

**ХАРАКТЕРИСТИКИ**

| | |
|---|---|
| **Наименование продукции:** | Dedalo - IP65 - 48W 3800K |
| **Код:** | NL17034VTW1 |
| **Серии:** | Outdoor |
| **Окружающая среда:** | Уличное |

**РАЗМЕРЫ**




**РАЗМЕРЫ**

| | |
|---|---|
| **Длина:** | cm 500 |
| **Ширина:** | cm 1 |
| **Высота:** | cm 0.3 |
| **Вес:** | kg 0.6 |

**ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ**

| | |
|---|---|
| **Категория:** | LED |
| **Ватт:** | 48W |
| **Типология:** | 0 |
| **Цветовая температура (K):** | 3800K |
| **Класс:** | A |

**LUMINAIR**

| | |
|---|---|
| **ПРА:** | Electronic supplied separately |
| **Watt:** | 48W |

### АКСЕССУАРЫ

ALIMENT. 40W 24Vdc IP67
NL62040

ALIMENT. 70W 24Vdc IP67
NL89080

ALIMENT. 70W 24Vdc NL87110

ALIMENT. 150W 24Vdc IP67
NL62880

DEDALO KIT CONNETTORI
NL170330