

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Ego 220 driver-over 6x54° 797 lm 3000K Round



ДИЗАЙН:

Nord Light
2011

МАТЕРИАЛЫ:

ОПИСАНИЕ:

Light fixture with high-performance LED light sources. Recessed floor installation. Walk-over version. Housing depths: Ego WO: 110mm - 120mm, Ego Flat WO: 60mm. Round and square version in five sizes. Consists of body, frame, black silkscreened tempered glass, recessing box. Body in EN AB44100 aluminium, silicone gaskets. Three colour options: with aluminium (only in the 50mm and 90mm size), stainless steel or black silkscreened tempered glass frame, 8mm thick, flush floor-mounting Recessing box for laying in reinforced polymer, can be ordered separately. Ego Flat WO-Feeding cable H05RN-F, with 300cm length for EGO 55 & EGO 90, 20cm for EGO 150, 30cm for EGO 220. Power connection to the mains by means of remote ballast and IP68 electrical terminal board, supplied with the fixture. Fixing to the recessing box is ensured by means of anti-vandal screws TORX, AISI 316. Glass surface temperature lower than 40°C. Fixed optics. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 2 colour temperatures: Warm = 3000K Neutral = 4000K Screws in stainless steel AISI 316. Painted die-cast aluminium with 3-stage outdoor treatment: nanotechnologies, antioxidant primer, polyester paint. Technical features of light fixtures in compliance with EN60598-1 and part 2-13. IP Rating IP65 IP67. Insulation class: Ego WO: class I. Ego Flat WO: class III. Installation must be carried out by specialized personnel. Carefully follow the instructions.

ВЫБРАТЬ

LED

Steel

КОД ПРОДУКТА

T4039ELPTW00 +
T409903

Вид светового потока

IP 65/67

Flood opticWide luminous flow suitable for lighting large areas.

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Ego 220 driver-over 6x54°
797 lm 3000K Round
Код: T4039ELPTW00 + T409903
Цвет: Steel
Серии: Nord Light, Outdoor

РАЗМЕРЫ

Диаметр: cm 22
Диаметр отверстия: cm 31.6
Глубина встройки: cm 11.7
Форма отверстия: Круглая форма
Ударопрочность: IK10


ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED
Ватт: 16 W
Световой поток (lm): 2108 lm
Типология: 1
Цветовая температура (K): 3000K
Класс: A

LUMINAIR

ПРА: Integrated electronic
ballast
Watt: 16 W

РАЗМЕРЫ



ЦВЕТ

