


## ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

### Ego 150S DL 5° 4000K



#### ДИЗАЙН:

Artemide  
2011

#### МАТЕРИАЛЫ:

#### ОПИСАНИЕ:

Light fixture with high-performance LED light sources. Ceiling installation. Two different housing depths. Round and square version in five sizes. Consists of body, frame, black silkscreened tempered glass, fixing springs. Body in EN AB44100 aluminium, silicone gaskets. Frame in aluminium or stainless steel AISI 316. Black silkscreened tempered glass, 8mm-thick. Fixing springs in harmonic iron. Power connection to the mains by means of a H05RN-r cabl and IP68 electrical terminal board, supplied with the fixture. Glass surface temperature lower than 40°C. Fixed optics. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 2 colour temperatures Warm = 3000K Neutral = 4000K Painted die-cast aluminium with 3-stage outdoortreatment: nanotechnologies, anti-oxidant primer, polyester paint. Technical features of light fixtures in compliance with EN60598-1 and part 2-13. IP Rating IP65. Insulation class III. Installation must be carried out by specialized personnel. Carefully follow the instructions.

Flood opticWide luminous flow suitable for lighting large areas.

#### ВЫБРАТЬ

LED

Aluminium

#### КОД ПРОДУКТА

T4120NSPN00

#### Вид светового потока

IP 65/67

#### ТЕХНИЧЕСКИЕ ДАННЫЕ

##### ХАРАКТЕРИСТИКИ

Наименование продукции: Ego 150S DL 5°  
4000K  
Код: T4120NSPN00  
Цвет: Aluminium  
Серии: Outdoor

##### ЦВЕТ



##### РАЗМЕРЫ

Длина базы: cm 15  
Ширина базы: cm 15  
Диаметр отверстия: cm 13.5  
Глубина встройки: cm 12.6  
Форма отверстия: Квадратная форма  
Ударопрочность: IK10

##### ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED  
Ватт: 8W  
Мощность (каждый): 2W  
Световой поток (lm): 437lm  
Количество: 1 x 4  
Типология: 1  
Цветовая температура (K): 4000K  
Класс: A

##### LUMINAIR

Watt: 8W

#### АКСЕССУАРЫ



