

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Nota Bene Ceiling 1200 Darklight - T16 54W Dimmable - White


ДИЗАЙН:

Artemide

МАТЕРИАЛЫ:

Painted Steel

ОПИСАНИЕ:

Single ceiling lights using 1x54W or 2x54W T16 fluorescent light source. Two lighting options: dark light and wall washer. Steel body with a white or grey paint finish. Electronic control gear, with or without dimming (Dali-Switchdim). Lamps can be maintained without removing the luminaire. Complies with standard EN60598-1 and other specific standards. Nota Bene ceiling dark light Super pure aluminum dark light optics. Dark light emission is in compliance with EN12464-1 standard, with average luminance levels lower than the 1000 cd/m² limit for an observation angle of 65° or above with respect to the vertical axis. Light output ratio 71%. Emergency lighting as an optional extra. Nota Bene ceiling wall washer Asymmetric aluminum reflector.

ВЫБРАТЬ

FLUO

White

КОД ПРОДУКТА

M109021

Вид светового потока


IP20

Dimmable

ТЕХНИЧЕСКИЕ ДАННЫЕ
ХАРАКТЕРИСТИКИ

Наименование продукции: Nota Bene Ceiling 1200 Darklight - T16 54W Dimmable - White


Код: M109021

Цвет: White

Материал: Painted Steel

Серии: Architectural

Окружающая среда: Внутреннее место контракта:

РАЗМЕРЫ

ОПТИКА

Вид светового потока: Direct

РАЗМЕРЫ

Длина: cm 1234

Ширина: cm 160

Высота: cm 186

Вес: kg 4.2

тест раскаленной проволокой: 850 °

ЦВЕТ

ЛАМПЫ НЕ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: FLUO

Количество: 1

Lbs: T16(G5)

Ватт: 54W

Цоколь: G5

Тип: FDH-54

Световой поток (lm): 4450lm

Цветопередача: 85

Цветовая температура (K): 3000K

Продолжительность (h): 20000h

LUMINAIR

ПРА: Electronic Dimmable DALI Integrated

Watt: 1x54W

Напряжение: 220V-240V



INTERACTIVE-DALI kit Ø86mm, white, recessed. Can be connected to a max. 11 DALI dimmable units. Is operated through INTERACTIVE-DALI remote control or external push button. M074030



INTERACTIVE-DALI remote control. M104900