

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Nota Bene Ceiling 1200 Darklight - T16 54W Dimmable - Grey



ДИЗАЙН:

Artemide

МАТЕРИАЛЫ:

Painted Steel

ОПИСАНИЕ:

Single ceiling lights using 1x54W or 2x54W T16 fluorescent light source. Two lighting options: dark light and wall washer. Steel body with a white or grey paint finish. Electronic control gear, with or without dimming (Dali-Switchdim). Lamps can be maintained without removing the luminaire. Complies with standard EN60598-1 and other specific standards. Nota Bene ceiling dark light Super pure aluminum dark light optics. Dark light emission is in compliance with EN12464-1 standard, with average luminance levels lower than the 1000 cd/m² limit for an observation angle of 65° or above with respect to the vertical axis. Light output ratio 71%. Emergency lighting as an optional extra. Nota Bene ceiling wall washer Asymmetric aluminum reflector.

ВЫБРАТЬ

FLUO

Grey

КОД ПРОДУКТА

M109091

Вид светового потока



IP20


Dimmable

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Nota Bene Ceiling 1200 Darklight - T16 54W Dimmable - Grey
 Код: M109091
 Цвет: Grey
 Материал: Painted Steel
 Серии: Architectural
 Окружающая среда: Внутреннее место контракта:

РАЗМЕРЫ



ОПТИКА

Вид светового потока: Direct

РАЗМЕРЫ

Длина: cm 123
 Ширина: cm 16
 Высота: cm 5.4
 Вес: kg 4.2
 тест раскаленной проволокой: 850 °

ЦВЕТ



ЛАМПЫ НЕ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: FLUO
 Количество: 1
 Lbs: T16(G5)
 Ватт: 54W
 Цоколь: G5
 Тип: FDH-54
 Световой поток (lm): 4450lm
 Цветопередача: 85
 Цветовая температура (K): 3000K
 Продолжительность (h): 20000h

LUMINAIR

ПРА: Electronic Dimmable DALI Integrated
 Watt: 1x54W
 Напряжение: 220V-240V



INTERACTIVE-DALI kit Ø86mm, white, recessed. Can be connected to a max. 11 DALI dimmable units. Is operated through INTERACTIVE-DALI remote control or external push button. M074030



INTERACTIVE-DALI remote control. M104900