


ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Nothing86 SA Suspension Led bianco 24W + 1x39W Diff - Direct+Indirect Emission - White



ДИЗАЙН:

Ernesto Gismondi

МАТЕРИАЛЫ:

Extruded Aluminium

ОПИСАНИЕ:

A versatile modular lighting system for linear diffused or dark light emission and freely configurable accent lighting. Composed of structural modules in extruded aluminium, prewired gear plates and optics systems. 3 types of installation: recessed, surface mounting and suspended. Structural modules available in 12 different lengths of up to 4736mm, specially designed to allow the lighting designer to alternate as freely as possible different light sources. The lighting sequence can also evolve over time to meet new arrangements, as long as it remains compatible with the initial total length installed. Linear fluorescent, led and metal halide technologies can be freely alternated. Prewired gear plates with quick-connectors, with direct fluorescent or LED lighting equipment, and indirect fluorescent illumination. 2 options of fluorescent diffused lighting available: T16-seamless lamps or conventional T16 lamps with overlapping arrangement for uninterrupted light lines without dark spots. 2 LED equipment options: monochromatic with warm white or neutral white emission, and RGB. Angular configurations possible by means of junction angles on the same plane or on 2 perpendicular planes (on request). Simple installations can be managed with "all-in-one" fixtures (nothing 86Stand-Alone) already pre-configured and fully accessorized. Complies with standard EN60598-1 and other specific standards.

Luminaire comes complete with power supply and DALI control unit .

ВЫБРАТЬ

FLUO LED

white

КОД ПРОДУКТА

M202620

Вид светового потока




ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Nothing86 SA Suspension
Led bianco 24W + 1x39W
Diff - Direct+Indirect
Emission - White
Код: M202620
Цвет: white
Материал: Extruded Aluminium
Серии: Architectural
Окружающая среда: Внутреннее

РАЗМЕРЫ



ЦВЕТ



РАЗМЕРЫ

Длина: cm 118
Ширина: cm 9.2
Высота: cm 12.5
Максимальная высота от потолка: cm 200
тест раскаленной проволокой: 650 °

ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED
Ватт: 20W
Световой поток (lm): 3075lm
Типология: 1
Цветовая температура (K): 4000K
Класс: A

ЛАМПЫ НЕ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: FLUO
Количество: 1
Lbs: T16
Ватт: 39W
Цоколь: G5
Тип: FDH-39
Световой поток (lm): 3100lm
Цветопередача: 85

Цветовая температура (K): 3000K

LUMINAIR

ПРА: Electronic Integrated
Наличие трансформатора: with DALI control
Watt: 24W + 1x39W
Напряжение: 220V-240V

АКСЕССУАРЫ



LAMPE FLUO T5 39W HO
3000°K M004380



LAMPE FLUO T5 39W HO
4000°K Ø16 G5 M004381