

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Nothing86 SA Suspension Led bianco 24W + 1x39W dali switch Diff - Direct+Indirect Emission - anodized



дизайн:

Ernesto Gismondi

материалы:

Extruded Aluminium

ОПИСАНИЕ:

A versatile modular lighting system for linear diffused or dark light emission and freely configurable accent lighting. Composed of structural modules in extruded aluminium, prewired gear plates and optics systems.3 types of installation: recessed, surface mounting and suspended. Structural modules available in 12 different lengths of up to 4736mm, specially designed to allow the lighting designer to alternate as freely as possible different light sources. The lighting sequence can also evolve over time to meet new arrangements, as long as it remains compatible with the initial total length installed.Linear fluorescent, led and metal halide technologies can be freely alternated.Prewired gear plates with quick-connectors, with direct fluorescent or LED lighting equipment, and indirect fluorescent illumination.2 options of fluorescent diffused lighting available: T16-seamless lamps or conventional T16 lamps with overlapping arrangement for uninterrupted light lines without dark spots.2 LED equipment options: monochromatic with warm white or neutral white emission, and RGB. Angular configurations possible by means of junction angles on the same plane or on 2 perpendicular planes (on request). Simple installations can be managed with "all-in-one" fixtures (nothing 86Stand-Alone) already pre-configured and fully accessorized. Complies with standard EN60598-1 and other specific standards

ВЫБРАТЬ

FLUO LED

anodized

КОД ПРОДУКТА

м202661

Вид светового потока





Luminaire comes complete with power supply and DALI control unit .

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Nothing86 SA Suspension

Led bianco 24W + 1x39W dali switch Diff -

Direct+Indirect Emission -

anodized

Код:M202661Цвет:anodized

Материал:Extruded AluminiumСерии:ArchitecturalОкружающая среда:Внутреннее

РАЗМЕРЫ

 Длина:
 cm 118

 Ширина:
 cm 9.2

 Высота:
 cm 12.5

 Максимальная высота от
 cm 200

потолка:

тест раскаленной 650 °

проволокой:

ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

 Категория:
 LED

 Ватт:
 20W

 Световой поток (lm):
 3075lm

 Типология:
 1


 Цветовая температура (K):
 4000K

 Класс:
 A

ЛАМПЫ НЕ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: FLUO
Количество: 1
Lbs: T16
Ватт: 39W
Цоколь: G5
Тип: FDH-39
Световой поток (Im): 3100Im

РАЗМЕРЫ







Цветопередача: 85 **Цветовая температура (K)**: 3000K

LUMINAIR

 ПРА:
 Electronic Integrated

 Наличие трансформатора:
 with DALI control

 Watt:
 24W + 1x39W

 Напряжение:
 220V-240V

АКСЕССУАРЫ

3=

LAMPE FLUO T5 39W HO 3000?K M004380

LAMPE FLUO T5 39W HO 4000°K Ø16 G5 M004381

3=