Artemide

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Nothing86System SA Ceiling Led Diff - 30W 3000K Dimmable - Anodized



ДИЗАЙН:

Ernesto Gismondi

МАТЕРИАЛЫ:

Extruded Aluminium

ОПИСАНИЕ:

A versatile modular lighting system for linear diffused or dark light emission and freely configurable accent lighting.Composed of structural modules in extruded aluminium, prewired gear plates and optics systems.3 types of installation: recessed, surface mounting and suspended.Structural modules available in 12 different lengths of up to 4736mm, specially designed to allow the lighting designer to alternate as freely as possible different light sources. The lighting sequence can also evolve over time to meet new arrangements, as long as it remains compatible with the initial total length installed.Linear fluorescent, led and metal halide technologies can be freely alternated.Pre-wired gear plates with quick-connectors, with direct fluorescent or LED lighting equipment, and indirect fluorescent illumination.2 options of fluorescent diffused lighting available: T16-seamless lamps or conventional T16 lamps with overlapping arrangement for uninterrupted light lines without dark spots.2 LED equipment options: monochromatic with warm white or neutral white emission, and RGB.Angular configurations possible by means of junction angles on the same plane or on 2 perpendicular planes (on request).Simple installations can be managed with “all-in-one” fixtures (nothing 86Stand-Alone) already pre-configured and fully accessorized.Complies with standard EN60598-1 and other specific standards.

Luminaire comes complete with DALI power supply unit.

ВЫБРАТЬ

LED

Anodized

КОД ПРОДУКТА

M203061

Вид светового потока

IP20

Dimmable

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции:	Nothing86System SA Ceiling Led Diff - 30W 3000K Dimmable - Anodized
Код:	M203061
Цвет:	Anodized
Материал:	Extruded Aluminium
Серии:	Architectural
Окружающая среда:	Внутреннее
место контракта:	Гостеприимство Гостиницы, Розничные магазины, Офисы

РАЗМЕРЫ

РАЗМЕРЫ

Длина:	cm 118
Ширина:	cm 9.2
Высота:	cm 12.5
тест раскаленной проволокой:	850 °

ЦВЕТ

ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория:	LED
Ватт:	20W
Световой поток (lm):	2600lm
Типология:	1
Цветовая температура (K):	4000K
Класс:	A

LUMINAIR

ПРА:	Electronic Dimmable Dali Integrated
Watt:	23W
Напряжение:	220V-240V