
## Artemide

### ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

## Nothing86System SA Suspension Led RGB 36W Diff - Direct+indirect Emission -White



#### дизайн:

Ernesto Gismondi


#### материалы:

Extruded Aluminium

#### ОПИСАНИЕ:

A versatile modular lighting system for linear diffused or dark light emission and freely configurable accent lighting. Composed of structural modules in extruded aluminium, prewired gear plates and optics systems.3 types of installation: recessed, surface mounting and suspended. Structural modules available in 12 different lengths of up to 4736mm, specially designed to allow the lighting designer to alternate as freely as possible different light sources. The lighting sequence can also evolve over time to meet new arrangements, as long as it remains compatible with the initial total length installed.Linear fluorescent, led and metal halide technologies can be freely alternated.Prewired gear plates with quick-connectors, with direct fluorescent or LED lighting equipment, and indirect fluorescent illumination.2 options of fluorescent diffused lighting available: T16-seamless lamps or conventional T16 lamps with overlapping arrangement for uninterrupted light lines without dark spots.2 LED equipment options: monochromatic with warm white or neutral white emission, and RGB. Angular configurations possible by means of junction angles on the same plane or on 2 perpendicular planes (on request). Simple installations can be managed with "all-in-one" fixtures (nothing 86Stand-Alone) already pre-configured and fully accessorized. Complies with standard EN60598-1 and other specific standards

Luminaire comes complete with power supply and DALI control unit. Indirect emission is not dimmable. Upper dust-protection polycarbonate screen is included.



#### Вид светового потока





#### ТЕХНИЧЕСКИЕ ДАННЫЕ

#### **ХАРАКТЕРИСТИКИ**

Наименование продукции: Nothing86System SA

Suspension Led RGB 36W Diff - Direct+indirect

Emission - White Код: M228420 White

Цвет: Extruded Aluminium Материал: Architectural Серии: Окружающая среда: Внутреннее

#### РАЗМЕРЫ

cm 237 Длина: Ширина: cm 9 2 Высота: cm 12.5 Максимальная высота от

650° тест раскаленной

проволокой:

# цвет

**РАЗМЕРЫ** 

#### ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: 42W Типология: **Цветовая температура (К)**: RGB Класс:

#### ЛАМПЫ НЕ ВКЛЮЧЕНЫ В КОМПЛЕКТ

FLUO Категория: Количество: Lbs: T16 39W Ватт: Цоколь: G5 FDH-39 Тип: Световой поток (Im): 3500lm

**Цветопередача**: 85 **Цветовая температура (K)**: 6500K

#### LUMINAIR

 ПРА:
 Electronic Integrated

 Наличие трансформатора:
 with DALI control

 Watt:
 42W + 1x39W

 Напряжение:
 220V-240V

АКСЕССУАРЫ

3=

LAMPE FLUO T5 39W HO 4000°K Ø16 G5 M004381 LAMPE FLUO T5 39W HO 3000?K M004380

3=