

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Nothing86System SA Ceiling Led RGB 21W Diff - Anodized



дизайн:

Ernesto Gismondi

материалы:

Extruded Aluminium

ОПИСАНИЕ:

A versatile modular lighting system for linear diffused or dark light emission and freely configurable accent lighting. Composed of structural modules in extruded aluminium, prewired gear plates and optics systems.3 types of installation: recessed, surface mounting and suspended. Structural modules available in 12 different lengths of up to 4736mm, specially designed to allow the lighting designer to alternate as freely as possible different light sources. The lighting sequence can also evolve over time to meet new arrangements, as long as it remains compatible with the initial total length installed.Linear fluorescent, led and metal halide technologies can be freely alternated.Prewired gear plates with quick-connectors, with direct fluorescent or LED lighting equipment, and indirect fluorescent illumination.2 options of fluorescent diffused lighting available: T16-seamless lamps or conventional T16 lamps with overlapping arrangement for uninterrupted light lines without dark spots.2 LED equipment options: monochromatic with warm white or neutral white emission, and RGB. Angular configurations possible by means of junction angles on the same plane or on 2 perpendicular planes (on request). Simple installations can be managed with "all-in-one" fixtures (nothing 86Stand-Alone) already pre-configured and fully accessorized. Complies with standard EN60598-1 and other specific standards

Luminaire comes complete with power supply and DALI control unit .

125

РАЗМЕРЫ







ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Nothing86System SA

Ceiling Led RGB 21W Diff -

Anodized M229360

Код: Цвет: Anodized Extruded Aluminium Материал:

Серии: Architectural Окружающая среда: Внутреннее место контракта: Гостеприимство Гостиницы, Розничные

магазины. Офисы

РАЗМЕРЫ

Дпина: cm 118 Ширина: cm 9.2 Высота: cm 12.5 тест раскаленной

проволокой:

цвет

Категория: Типология: **Цветовая температура (К)**: RGB Класс:

ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

LUMINAIR

ПРА: Electronic Integrated Наличие трансформатора: with DALI control

21W 220V-240V Напряжение: