


ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Nothing86System SA Suspension Led bianco 23W Diff - Direct Emission - White



ДИЗАЙН:

Ernesto Gismondi

МАТЕРИАЛЫ:

Extruded Aluminium

ОПИСАНИЕ:

A versatile modular lighting system for linear diffused or dark light emission and freely configurable accent lighting. Composed of structural modules in extruded aluminium, prewired gear plates and optics systems. 3 types of installation: recessed, surface mounting and suspended. Structural modules available in 12 different lengths of up to 4736mm, specially designed to allow the lighting designer to alternate as freely as possible different light sources. The lighting sequence can also evolve over time to meet new arrangements, as long as it remains compatible with the initial total length installed. Linear fluorescent, led and metal halide technologies can be freely alternated. Prewired gear plates with quick-connectors, with direct fluorescent or LED lighting equipment, and indirect fluorescent illumination. 2 options of fluorescent diffused lighting available: T16-seamless lamps or conventional T16 lamps with overlapping arrangement for uninterrupted light lines without dark spots. 2 LED equipment options: monochromatic with warm white or neutral white emission, and RGB. Angular configurations possible by means of junction angles on the same plane or on 2 perpendicular planes (on request). Simple installations can be managed with "all-in-one" fixtures (nothing 86Stand-Alone) already pre-configured and fully accessorized. Complies with standard EN60598-1 and other specific standards.

Luminaire comes complete with power supply and DALI control unit .

ВЫБРАТЬ

LED

Anodized

КОД ПРОДУКТА

M2900W20

Вид светового потока



ТЕХНИЧЕСКИЕ ДАННЫЕ	
ХАРАКТЕРИСТИКИ Наименование продукции: Nothing86System SA Suspension Led bianco 23W Diff - Direct Emission - White Код: M2900W20 Цвет: Anodized Материал: Extruded Aluminium Серии: Architectural Окружающая среда: Внутреннее РАЗМЕРЫ Длина: cm 118 Ширина: cm 9.2 Высота: cm 12.5 Максимальная высота от потолка: cm 200 тест раскаленной проволокой: 850 ° ЦВЕТ ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ Категория: LED Ватт: 23W Световой поток (lm): 2440lm Типология: 1 Цветовая температура (K): 3000K Класс: A LUMINAIR ПРА: Electronic Integrated Наличие трансформатора: with DALI control Watt: 23W Напряжение: 220V-240V РАЗМЕРЫ	

АКСЕССУАРЫ



LAMPE FLUO T5 39W HO
3000°K M004380



LAMPE FLUO T5 39W HO
4000°K Ø16 G5 M004381